

Product: 6342PC ☑



Security & Sound, 3 Pair 18 AWG, BC, Individually Shielded, CMP

Product Description

Security, Pro Audio & Intercom Cable, Plenum-CMP, 3-18 AWG stranded bare copper pairs with FEP insulation, Individually Beldfoil® shielded and Flamarrest® jacket

Technical Specifications

Construction Details

Element	Number of Element	Size	Stranding	Material
Pair(s)	3	18 AWG	7x26	BC - Bare Copper

Insulation

Conductor

Element Material		Nom. Thickness	Nom. Insulation Diameter	Color Code	
Pair(s)	FEP - Fluorinated Ethylene Propylene	0.01 in (0.25 mm)	0.066 in (1.7 mm)	Black & Red, Black & White, Black & Green	

Inner Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

Outer Shield

Material No Shield

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter	Ripcord
F	PVC - Polyvinyl Chloride	0.0165 in (0.419 mm)	0.3 in	Yes
(Overall Cable Diameter (I	Nominal):	0.300 in	

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current	
6.93 Ohm/1000ft	14.4 Ohm/1000ft (47.2 Ohm/km)	44 pF/ft (140 pF/m)	79.2 pF/ft (260 pF/m)	9.8 Amps per Conductor at 30°C	

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Stationary Min. Installation Min.

3 (76)		
Max. Pull Tension:	139.9 lbs	
Bulk Cable Weight:	58 lbs/1000ft	

Standards and Compliance

2 in (76 mm) 2 in

Environmental Suitability:	Indoor - Plenum, Indoor	
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6	
NEC / UL Compliance:	Article 800, CMP	
CEC / C(UL) Compliance:	CMP	
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

History

Update and Revision:	Revision Number: 0.369 Revision Date: 12-21-2021	

Variants

Item #	Color	Putup Type	Length	UPC
6342PC 8771000	Natural	Reel	1,000 ft	612825176404

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

01342.35T.01 01364.35T.01 CS2885-000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 644833-000 6500FE-877-1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CY0660-000 730859-000 MCC-USB-4-250 768146-000 773159-000 820457-000 82907-NAT-500 83005-WHT-500 83023-YEL-500 83027-RED-100 83029-GRN-100 8302-CHR-500 83046-RED-100 8305-CHR-100 83333-WHT-100 8334-060-1000 83652-RED-100 8404-060-500 8434-CHR-100 8441-BLK-1000 8450-BLK-1000 8451-GRY-U500 8459-CHR-500 8465-CHR-1000 8466-CHR-1000 8467-CHR-1000 8469 060100 8469-CHR-1000 8471-CHR-1000 8472-BLK-250 8473-CHR-U500 8501-ORG-100 8501-RED-100 8502-GRY-100 8503-WHT/BLU-100 8520-BRN-100 8520-GRY-100 8523-GRY-100 8523-GRY-1000