



Product: <u>73405W</u> ☑

MachFlex™, 5 C #14 Str BC, PVC Ins, PVC Jkt, AWM 2587 CLASS K

Request Sample

Product Description

MachFlex™ for Moderate Flex, 5 Conductor 14AWG (41x30) Bare Copper, PVC Insulation, PVC Outer Jacket, AWM 2587 CLASS K

Technical Specifications

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Conductor(s)	4	14	41x30	BC - Bare Copper
Ground	1	14	41x30	BC - Bare Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	0.022 in (0.56 mm)	0.118 in (3.00 mm)	Black and Numbered
Ground	PVC - Polyvinyl Chloride	0.022 in (0.56 mm)	0.118 in (3.00 mm)	Yellow/Green

Outer Shield

Shield Type	Material
No Shield	No Shield

Outer Jacket

Separator	Material	Nom. Thickness	Nom. Diameter
Paper Tape	PVC - Polyvinyl Chloride	0.055 in (1.4 mm)	0.439 in
Overall Cabl	le Diameter (Nominal): 0.4	439 in (11.2 mm)	

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	2.6 Ohm/1000ft	36 pF/ft (120 pF/m)	20 Amps per Conductor at 30°C
Ground Wire	2.62 Ohm/1000ft (8.60 Ohm/km)		

Voltage

UL Voltage Rating 600 V

Mechanical Characteristics

Temperature

UL Temperature	Operating		
90°C	-40°C To 90°C (Static), -5°C To 90°C (Flexing)		

Bend Radius

Flexing Min.
2.2 in (56 mm)

Max. Pull Tension: 161 lbs

258 lbs/1000ft	: 258 lbs/1000ft	Bulk Cable Weight:
----------------	------------------	--------------------

Standards and Compliance

Environmental Suitability:	Oil Resistance	
Flammability / Reaction to Fire:	FT1	
AWM Compliance:	AWM 2587, AWM I/II A/B	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	: China RoHS II (GB/T 26572-2011)	
Other Standard Compliance(s):	VDE 0472, Section 803 Oil Test	

History

Update and Revision:	Revision Number: 0.135 Revision Date: 12-20-2021

Variants

Item #	Color	Putup Type	UPC
73405W 008100	Gray	Reel	612825409557
73405W 0081000	Gray	Reel	612825409564

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

000581-000 00100004 00100014 00100024 00100034 0010004 0010005 0010006 0010007 0010008 0010009 0010012 00100214 00100224 00100234 00100244 0010025 0010026 0010027 0010028 0010029 0010030 0010031 0010032 0010034 00100414 00100424 00100434 0010044 0010045 0010046 0010047 0010049 0010050 0010052 0010053 0010054 0010056 00100634 00100644 00100654 00100664 0010068 0010069 0010071 0010072 0010074 0010076 0010086 0010087