

**Product:** <u>8019</u> ☑

Bus Bar Wire, #18 Sol TC

# **Product Description**

Bus Bar Wire, 18AWG (Solid) Tinned Copper, QQ-W-343G

## **Technical Specifications**

## **Product Overview**

table Applications: bus bar
-----------------------------

## **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of C	onductors
18	Solid	TC - Tinned Copper	1	
Conductor Count:			1	

## **Construction and Dimensions**

Circular Mil Area (CMA)1:	1648
---------------------------	------

# **Electrical Characteristics**

# Conductor DCR



# **Mechanical Characteristics**

Bulk Cable Weight:	6 lbs/1000ft
Min. Bend Radius/Minor Axis:	0.16 in

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
CA Prop 65:	Yes
MII Order #39 (China RoHS):	Yes

#### Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A

# Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

#### **Part Number**

#### Variants

Item #	Color	Put-Up Type	Length	UPC
8019 000100	None	Reel	100 ft	612825194309
8019 0001000	None	Reel	1,000 ft	612825194316

## **History**

Update and Revision: Revision Number: 0.343 Revision Date: 12-15-2021

© 2022 Belden, Inc.

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

8918-BRN-1000 8920-DK-BLU-1000 CR6328-000 01776.38.01 M22759/16-14-5-500FT 7053-RED-1000 7053-SLATE-1000 F25935-000 F60898-000 8055 81044/12-18-9CS3209 82A0811-4-9-G110 83004-ORG-1000 83005-LT-BLU-1000 83025-VIO-1000 8523-RED-100 8524-WHT-100 8525-ORG-1000 8530-BLK-1000 8530-LT-BLU-100 8538-009-1000 8597-LT-BLU-100 8898-BLK-100 138498-000 E76065-000 EPD50886A-20-9 BFWUL3239-24-PINK C2015A.12.04 C2015A.12.05 C2015A.12.08 C2015A.12.10 C2015A.12.19 C2016A.12.05 C2016A.12.07 C2065A.12.02 C77653-000 220368-001 8916-GRY-500 8918-RED-100 8919-DK-BLU-1000 8919-YEL-100 8920-YEL-100 9242833001 933205-000 2841/7-YELLOW-1000 2842/7-ORANGE-100 2842/7-RED-1000 2843/19-BLUE-100 2843/1-YELLOW-1000 2843/7-GREEN-100