## **Detailed Specifications & Technical Data**

**ENGLISH MEASUREMENT VERSION** 



### 8073 Hook-up/Lead - Magnet Wire

Picture Not Available For more Information please call

1-800-Belden1



### **General Description:**

The Poly-Thermaleze® base coat is a cross-linked, modified polyester. Its top coat is an amide-imide polymer. Rated for 200°C usage, Belden heavy-armored Poly-Thermaleze has exceptional ability to resist solvents and abuse in difficult windings.

### **Physical Characteristics (Overall)** Conductor AWG: # Conductors AWG Stranding Conductor Material Solid BC - Bare Copper **Total Number of Conductors:** Insulation Material: **Insulation Material** Polyester-Imide or Polyester-Amide-Imide Overcoated w/Polyamide-Imide Min. Increase in OD: 0.003 in **Overall Cable Overall Maximum Diameter:** .0682 **Mechanical Characteristics (Overall)** Operating Temperature Range: 200°C 12.500 lbs/1000 ft. **Bulk Cable Weight:** Approximate Length: 80 Turns Per Linear Inch: 14.9 Turns Per Square Inch: Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs** EU Directive 2011/65/EU (ROHS II): Yes EU Directive 2000/53/EC (ELV): Yes EU Directive 2002/95/EC (RoHS): Yes 01/01/2004 EU RoHS Compliance Date (mm/dd/yyyy): EU Directive 2002/96/EC (WEEE): Yes EU Directive 2003/11/EC (BFR): Yes CA Prop 65 (CJ for Wire & Cable): MII Order #39 (China RoHS): Yes J-W-1177/14 Military Specification: MIL Spec Rating: Class 200, Type K2 (Heavy) **NEMA Specification:** NEMA-MW-35-C (Heavy) Plenum/Non-Plenum Plenum (Y/N): No

Electrical Characteristics (Overall)
Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.500

Max. Recommended Current:

Page 1 of 2 08-26-2016

## **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



## 8073 Hook-up/Lead - Magnet Wire

Current 5.9 A

Breakdown Voltage:

6325 volts minimum at room temperature.

### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8073	1 EA	100.220 LB			#14 HVY ARM PT MAG WIRE

Revision Date: 01-21-2013 Revision Number: 2

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, without no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000
BFWUL3239-24-PINK 22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 284711-000 961473-000 30802-009-250 99M0111-20-2
A00594-000 190571-000 22759/41-12-9CS2620 22759/41-16-9CS2620 22759/43-10-9CS2873 265925-000 CM9524-000 31510-010-250
31514-009-500 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007 400R0111-10-9 431660-000 ATFC0311-20-0 44/7024-26-9-9
44A0112-22-9CS3184 456157-000 BFW-UL3239-24-WHITE 55/0312-26-6L-CS2570 55A0811-12-9 55A6087-20-9-9-9 55A6315-22-99CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5 55PC0211-20-5CS2502 55PC0811-6-9CS2637 55PC1211-22-9-9CS3278 C07683-000
32820-009-5000 34020-008-2000 391850-BK199 392075-RD199