

Product: [8263](#) 

Analog Video, RG59, #23 Solid BCCS, 95% BC Braid, PVC Jacket, CMX



Product Description

23 AWG solid bare copper-covered steel conductor, polyethylene insulation, bare copper braid shield (95% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Nominal Diameter | No. of Coax |
|-----|-----------|----------------------------------|------------------|-------------|
| 23 | Solid | BCCS - Bare Copper Covered Steel | 0.023 in | 1 |

Conductor Count:

Insulation

| Material | Nominal Diameter |
|-------------------|------------------|
| PE - Polyethylene | 0.146 in |

Outer Shield Material

| Type | Material | Coverage [%] |
|-------|------------------|--------------|
| Braid | Bare Copper (BC) | 95% |

Outer Jacket Material

| Material | Nominal Diameter |
|--|------------------|
| PVC - Polyvinyl Chloride (Non-Contaminating) | 0.241 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Conductor DCR | Conductor Resistance | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|-----------------------|----------------------|--------------------------|---------------------|
| 49 Ohm/1000ft | 49 Ohm/1000ft | | 2.6 Ohm/1000ft | 2.6 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 20.5 pF/ft |

Inductance

| Nominal Inductance |
|--------------------|
| 0.115 μ H/ft |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 75 Ohm |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 1 MHz | 0.6 dB/100ft |
| 10 MHz | 1.1 dB/100ft |

| | |
|----------|---------------|
| 50 MHz | 2.4 dB/100ft |
| 100 MHz | 3.4 dB/100ft |
| 200 MHz | 4.9 dB/100ft |
| 400 MHz | 7 dB/100ft |
| 700 MHz | 9.7 dB/100ft |
| 900 MHz | 11.1 dB/100ft |
| 1000 MHz | 12 dB/100ft |

Delay

| Nominal Delay |
|---------------|
| 1.54 ns/ft |

Voltage

| Non-UL Voltage Rating | UL Voltage Rating |
|-----------------------|-------------------|
| 1700 V RMS | 150 V RMS |

Temperature Range

| | |
|-----------------------|----------------|
| Non-UL Temp Rating: | 60°C |
| Operating Temp Range: | -40°C To +60°C |

Mechanical Characteristics

| | |
|-----------------------------|---------------|
| Bulk Cable Weight: | 36 lbs/1000ft |
| Max. Pull Tension: | 78 lbs |
| Min Bend Radius/Minor Axis: | 2.5 in |

Standards

| | |
|--------------------------|---------------------------|
| NEC/(UL) Compliance: | CMX |
| CEC/C(UL) Compliance: | CMX |
| UL AWM Style Compliance: | UL Style 1354 (30 V 60°C) |
| CPR Euroclass: | Eca |
| RG Type: | 59B/U Type |
| Series Type: | 59 |
| Military Compliance: | Mil-C-17D |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| Environmental Space: | Indoor/Outdoor |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-01 |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|---------------|
| UL Flammability: | VW-1 |
| IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating: | 150 V RMS |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|-------|------------|----------|--------------|
| 8263 010U500 | Black | UnReel | 500 ft | 612825197515 |
| 8263 0101000 | Black | Reel | 1,000 ft | 612825356004 |
| 8263 010U1000 | Black | UnReel | 1,000 ft | 612825358718 |

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision: Revision Number: 0.243 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [633948-877-1000](#) [CY2389-000](#) [8213-010-1000](#) [8221-010-U1000](#) [8233-010-1000](#) [88281-010-500](#) [1322R-010-1000](#) [177799-000](#) [1807A-B59-U1000](#) [9167-010-1000](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [9659-010-1000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [8-1616396-1](#) [8263-010-U1000](#) [8263 010U500](#) [8268-010-500](#) [8262 010U1000](#) [7915A 009U1000](#) [5024A1311-0](#) [TRC-75-1](#) [1281S5 010250](#) [1281S5 000250](#) [1530A 010U1000](#) [1505A 0081000](#) [9248 010U1000](#) [CO-142BNCX200-001](#) [7809WB 010500](#) [9244 0101000](#) [1694A 0081000](#) [9204 0101000](#) [8241F J5C1000](#) [1530A 0101000](#) [1674A TIN50](#) [7915A 0091000](#) [7915A 010500](#) [TWCH-78-2](#) [TWC-78-1](#)