

**Product: 8403** ☑





## **Product Description**

Microphone Cable, 3 Conductor 20 AWG (19 x 32) Tinned Copper (High conductivity), PE Insulation, Rayon Braid, 90% Tinned Copper Braid Shield, PVC Jacket

# **Technical Specifications**

#### **Product Overview**

	Suitable Applications:	Low frequency microphone or musical instruments; Balanced analog audio
--	------------------------	--

## **Construction Details**

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	3	20	19x32	TC - Tinned Copper (High Conductivity)

#### Insulation

Element	Material	Thickness [in.]	Color Code	
Conductor(s)	PE - Polyethylene	0.016	Clear, Black, Red	

# Outer Shield Material

Shield Type	Material	Coverage
Braid + Braid	Rayon + Tinned Copper (TC)	90%

#### **Outer Jacket Material**

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.033 in	0.244 in
Cable Diameter (Nominal	):	0.244 in

# **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	10.2 Ohm/1000ft	25 pF/ft	45 pF/ft	3.1 Amps per conductor @ 25°C
Nom Outer Sh	nield DCR:	3.5 Ohm/1000ft		

#### Voltage

Non-UL Voltage Rating

# **Mechanical Characteristics**

#### Temperature

UL Rating	Operating
60°C	-20°C to +80°C

#### Bend Radius

Stationary Will.	ilistaliation will.
2.5 in	2.9 in
Max. Pull Tension	n:
Bulk Cable Weigh	ht:
bulk Cable Weigi	nt.

## **Standards and Compliance**

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Fire Resistance:	VW-1
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

# History

Update and Revision:

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

89182-010-1000 89705-008-500 89842-002-1000 6000FE-877-1000 6120UL-002-1000 CS2885-000 M27500-20SP2S23 6300FE-877-U1000 6309UE-877-1000 M3905-BK005 6502FE 8771000 6541PA-008-U1000 CV6807-000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 752687-000 768146-000 773159-000 82841-877-5000 83318E-009-500 8348-060-500 83559-002-1000 83653-002-5000 83659-002-1000 83709-002-1000 8404-060-500 8469 060100 858171-000 8628-060-500 868361-001 8730-060-1000 8737-060-U1000 8747-060-100 8747-060-1000 8769-060-1000 8775-060-500 8780-060-1000 8782-001-U1000 88444-002-1000 9159-060-500 9318-060-1000 939870-000 9423 060U500