

Product: [8405](#) 



Microphone Cable, 5 Conductor 20 AWG, TC

Product Description

Mic, 20 AWG stranded (19x32) high-conductivity TC conductors, cabled, polyethylene insulation, rayon braid, TC braid shield (85% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
20	19x32	TC - Tinned Copper (High Conductivity)	0.037 in	5

Conductor Count:	5
------------------	---

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PE - Polyethylene	0.069 in	0.016 in

Color Chart

Number	Color
1	Black
2	Clear
3	Green
4	Red
5	Blue

Outer Shield

Type	Material	Coverage [%]
Braid	Rayon®	85%
Braid	Tinned Copper (TC)	85%

Outer Jacket

Material	Nominal Diameter	Min. Wall Thickness	Nominal Wall Thickness	Separator Material
PVC - Polyvinyl Chloride	0.281 in	0.005 in	0.035 in	Cotton Serve

Construction and Dimensions

Cabling

Filler
Jute

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR
10.2 Ohm/1000ft	10.2 Ohm/1000ft		3.47 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
23 pF/ft	40 pF/ft

Current

Max. Recommended Current [A]
3.2 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V RMS (UL AWM Style 2094)

Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-20°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	59 lbs/1000ft
Max. Pull Tension:	139 lbs
Min. Bend Radius/Minor Axis:	2.8 in

Standards

UL AWM Style Compliance:	UL Style 2094 (300 V 60°C)
--------------------------	----------------------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading, VW-1
UL voltage rating:	300 V RMS (UL AWM Style 2094)

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Put-Up Type	Length	UPC
8405 060250	Chrome	Reel	250 ft	612825206224
8405 060500	Chrome	Reel	500 ft	612825206231
8405 0601000	Chrome	Reel	1,000 ft	612825206217

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.377 Revision Date: 12-15-2021
----------------------	--

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[000581-000](#) [00100004](#) [00100014](#) [00100024](#) [00100034](#) [0010004](#) [0010005](#) [0010006](#) [0010007](#) [0010008](#) [0010009](#) [0010012](#) [00100214](#)
[00100224](#) [00100234](#) [00100244](#) [0010025](#) [0010026](#) [0010027](#) [0010028](#) [0010029](#) [0010030](#) [0010031](#) [0010032](#) [0010034](#) [00100414](#) [00100424](#)
[00100434](#) [00100444](#) [0010045](#) [0010046](#) [0010047](#) [0010049](#) [0010050](#) [0010052](#) [0010053](#) [0010054](#) [0010056](#) [00100634](#) [00100644](#) [00100654](#)
[00100664](#) [0010068](#) [0010069](#) [0010071](#) [0010072](#) [0010074](#) [0010076](#) [0010086](#) [0010087](#)