



REPRESENTATIVE IMAGE

**Product:** [8451](#)

Audio & Instrumentation, 1 Pair 22 AWG, TC, O/A Foil, CM

## Product Description

1 Pair 22 AWG stranded (7x30) TC conductors, polypropylene insulation, paper wrap, twisted pair, overall Beldfoil® shield (100% coverage), 22 AWG stranded TC drain wire, PVC jacket.

## Technical Specifications

### Product Overview

|                        |  |
|------------------------|--|
| Suitable Applications: | for use with automatic stripping equipments; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring |
|------------------------|--|

### Construction Details

#### Conductor

| Element | Number of Element | Size   | Stranding | Material           |
|---------|-------------------|--------|-----------|--------------------|
| Pair(s) | 1                 | 22 AWG | 7x30      | TC - Tinned Copper |

#### Insulation

| Element | Material           | Nom. Thickness     | Color Code  |
|---------|--------------------|--------------------|-------------|
| Pair(s) | PP - Polypropylene | 0.009 in (0.23 mm) | Black & Red |

#### Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 22 AWG (7x30) TC |

#### Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.020 in (0.51 mm) | 0.138 in (3.51 mm) |

Overall Cable Diameter (Nominal): 0.138 in (3.51 mm)

### Electrical Characteristics

#### Electricals

| Element | Nom. Conductor DCR            | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedance | Nom. Velocity of Prop. | Max. Current                   |
|---------|-------------------------------|-------------------------------|---|-------------------------------|------------------------|--------------------------------|
| Pair(s) | 14.5 Ohm/1000ft (47.6 Ohm/km) | 34 pF/ft (110 pF/m)           | 67 pF/ft (220 pF/m)                             | 45 Ohm                        | 66%                    | 2.9 Amps per Conductor at 25°C |

#### Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS         |

### Mechanical Characteristics

#### Temperature

| Operating      |
|----------------|
| -20°C To +75°C |

#### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 1.4 in (36 mm)  | 1.4 in (36 mm)    |

|                    |                          |
|--------------------|--------------------------|
| Max. Pull Tension: | 27 lbs                   |
| Bulk Cable Weight: | 13 lbs/1000ft (19 kg/km) |

## Standards and Compliance

|                                  |   |
|----------------------------------|---|
| Environmental Suitability:       | Indoor - Riser, Indoor  |
| Flammability / Reaction to Fire: | UL1666 Vertical Shaft, FT4, IEC 60332-1-2   |
| CPR Compliance:                  | CPR Euroclass: Eca  |
| NEC / UL Compliance:             | Article 800, CMR  |
| CEC / C(UL) Compliance:          | CMG   |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)   |

## Product Notes

|        |  |
|--------|--|
| Notes: | Unique paper separator facilitates jacket stripping. |
|--------|--|

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.359 Revision Date: 12-15-2021 |
|----------------------|--|

## Variants

| Item #        | Color | Putup Type   | Length    | UPC          |
|---------------|-------|--------------|-----------|--------------|
| 8451 010100   | Black | Reel         | 100 ft    | 612825207726 |
| 8451 010500   | Black | Reel         | 500 ft    | 612825207764 |
| 8451 010U500  | Black | UnReel       | 500 ft    | 612825427414 |
| 8451 0101000  | Black | Reel         | 1,000 ft  | 612825207733 |
| 8451 010U1000 | Black | UnReel       | 1,000 ft  | 612825207702 |
| 8451 010Z1000 | Black | ReelTuff Box | 1,000 ft  | 612825208129 |
| 8451 01015000 | Black | Reel         | 5,000 ft  | 612825207757 |
| 8451 0105000  | Black | Reel         | 5,000 ft  | 612825207696 |
| 8451 01010000 | Black | Reel         | 10,000 ft | 612825207740 |
| 8451 008500   | Gray  | Reel         | 500 ft    | 612825207658 |
| 8451 008U500  | Gray  | UnReel       | 500 ft    | 612825427407 |
| 8451 0081000  | Gray  | Reel         | 1,000 ft  | 612825207689 |
| 8451 008U1000 | Gray  | UnReel       | 1,000 ft  | 612825207665 |
| 8451 008Z1000 | Gray  | ReelTuff Box | 1,000 ft  | 612825207719 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Belden](#) manufacturer:*

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#) [CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#) [CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [706/2R-BLACK-EACH](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-1000](#) [8125-CHR-100](#) [8164-CHR-1000](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#) [83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#)