Detailed Specifications & Technical Data



8522 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

For more Information please call



1-800-Belden1



General Description:

Tinned copper, PVC insulation, medium wall. The extruded PVC insulation is flame and ozone resistant. Inert to most chemicals, oils, and solvents. Covers single cond., PVC insulated hook-up wire for internal wiring of electrical and electronic equipment.

| Physical Characteristics (Overall) Conductor AWG: | |
|---|---------------------|
| # Conductors AWG Stranding Conductor Material | |
| 1 18 16x30 TC - Tinned Copper | |
| Total Number of Conductors: | 1 |
| Insulation Insulation Material: | |
| Insulation Material Wall Thickness (mm) | |
| PVC - Polyvinyl Chloride 0.4318 | |
| Overall Insulation Overall Cable | |
| Overall Nominal Diameter: | 2.032 mm |
| Mechanical Characteristics (Overall) | |
| Operating Temperature Range: | -40°C To +80°C |
| Bulk Cable Weight: | 10.417 Kg/Km |
| Applicable Specifications and Agency Co | ompliance (Overall) |
| Applicable Standards & Environmental Prog | |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Military Specification: | MIL-W-76C type MWP |
| MIL Spec Rating: | 1000 V, 80°C |
| Plenum/Non-Plenum | |
| | No |

Nom. Conductor DC Resistance:

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

8522 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

DCR @ 20°C (Ohm/km)

20.834

Max. Operating Voltage - Other:

Voltage Description

1000 V RMS | Mil-W-76C

Max. Recommended Current:

| Description | Current | |
|--|---------|--|
| Single conductor in free air @ 30C ambient | 16 amps | |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------------|----------|-------------|--------------------|-------|------------------------|
| 8522 001100 | 100 FT | 0.800 LB | BROWN | | 18 STR PVC BRN |
| 8522 0011000 | 1,000 FT | 8.000 LB | BROWN | P | 18 STR PVC BRN |
| 8522 002100 | 100 FT | 0.800 LB | RED | | 18 STR PVC RED |
| 8522 0021000 | 1,000 FT | 8.000 LB | RED | P | 18 STR PVC RED |
| 8522 003100 | 100 FT | 0.800 LB | ORANGE | | 18 STR PVC ORG |
| 8522 0031000 | 1,000 FT | 8.000 LB | ORANGE | P | 18 STR PVC ORG |
| 8522 004100 | 100 FT | 0.800 LB | YELLOW | | 18 STR PVC YEL |
| 8522 0041000 | 1,000 FT | 8.000 LB | YELLOW | Р | 18 STR PVC YEL |
| 8522 005100 | 100 FT | 0.800 LB | GREEN, DARK | | 18 STR PVC GRN |
| 8522 0051000 | 1,000 FT | 8.000 LB | GREEN, DARK | P | 18 STR PVC GRN |
| 8522 006100 | 100 FT | 0.800 LB | BLUE, LIGHT | | 18 STR PVC LBLU |
| 8522 0061000 | 1,000 FT | 8.000 LB | BLUE, LIGHT | P | 18 STR PVC LBLU |
| 8522 007100 | 100 FT | 0.800 LB | VIOLET | | 18 STR PVC VIO |
| 8522 0071000 | 1,000 FT | 8.000 LB | VIOLET | P | 18 STR PVC VIO |
| 8522 008100 | 100 FT | 0.800 LB | GRAY | | 18 STR PVC GRY |
| 8522 0081000 | 1,000 FT | 8.000 LB | GRAY | P | 18 STR PVC GRY |
| 8522 009100 | 100 FT | 0.800 LB | WHITE | | 18 STR PVC WHT |
| 8522 0091000 | 1,000 FT | 8.000 LB | WHITE | P | 18 STR PVC WHT |
| 8522 010100 | 100 FT | 0.800 LB | BLACK | | 18 STR PVC BLK |
| 8522 0101000 | 1,000 FT | 8.000 LB | BLACK | Р | 18 STR PVC BLK |
| 8522 0111000 | 1,000 FT | 8.000 LB | TAN | P | 18 STR PVC TAN |
| 8522 0121000 | 1,000 FT | 8.000 LB | PINK | P | 18 STR PVC PNK |
| 8522 013100 | 100 FT | 0.800 LB | BLUE, DARK | | 18 STR PVC DBLU |
| 8522 0131000 | 1,000 FT | 8.000 LB | BLUE, DARK | P | 18 STR PVC DBLU |
| 8522 014100 | 100 FT | 0.800 LB | WHITE/BLACK | A | 18 STR PVC WHT/BLK |
| 8522 0141000 | 1,000 FT | 8.000 LB | WHITE/BLACK | A | 18 STR PVC WHT/BLK |
| 8522 0151000 | 1,000 FT | 8.000 LB | WHITE/RED | A | 18 STR PVC WHT/RED |
| 8522 0161000 | 1,000 FT | 8.000 LB | WHITE/GREEN | A | 18 STR PVC WHT/GRN |
| 8522 018100 | 100 FT | 0.800 LB | WHITE/BLUE | A | 18 STR PVC WHT/BLU |
| 8522 0181000 | 1,000 FT | 8.000 LB | WHITE/BLUE | A | 18 STR PVC WHT/BLU |
| 8522 0201000 | 1,000 FT | 8.000 LB | WHITE/ORANGE | A | 18 STR PVC WHT/ORG |
| 8522 0261000 | 1,000 FT | 8.000 LB | WHITE/BLACK/BLUE | A | 18 STR PVC WHT/BLK/BLU |
| 8522 0301000 | 1,000 FT | 8.000 LB | WHITE/BLACK/VIOLET | A | 18 STR PVC WHT/BLK/VIO |

Notes:

A = STOCKED STRIPE COLORS.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 09-03-2013

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

8522 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 CR6328-000
 01776.38.01
 M22759/16-14-5-500FT
 7053-RED-1000
 7053-SLATE-1000
 F25935-000

 F60898-000
 8055
 81044/12-18-9CS3209
 82A0811-4-9-G110
 83004-ORG-1000
 83005-LT-BLU-1000
 83025-VIO-1000
 8523-RED-100

 8524-WHT-100
 8525-ORG-1000
 8530-BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 8898-BLK-100
 138498-000

 E76065-000
 EPD50886A-20-9
 BFWUL3239-24-PINK
 C2015A.12.04
 C2015A.12.05
 C2015A.12.10
 C2015A.12.19

 C2016A.12.05
 C2016A.12.07
 C2065A.12.02
 C77653-000
 220368-001
 8916-GRY-500
 8918-RED-100
 8919-DK-BLU-100
 8919-YEL-100

 8920-YEL-100
 9242833001
 933205-000
 2841/7-YELLOW-1000
 2842/7-ORANGE-100
 2842/7-RED-1000
 2843/19-BLUE-100
 2843/1

 YELLOW-100
 2843/7-GREEN-100
 100
 100
 100
 100
 100
 100
 100