



REPRESENTATIVE IMAGE

Product: [8618](#)

Electronic, 3 C #16 Str TC, PE Ins, OS, PVC Jkt, CL3

[Request Sample](#)

Product Description

Electronic, 3 Conductor 16AWG (19x29) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CL3

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring |
|------------------------|---|

Construction Details

Conductor

| Element | Number of Element | Size | Stranding | Material |
|--------------|-------------------|--------|-----------|--------------------|
| Conductor(s) | 3 | 16 AWG | 19x29 | TC - Tinned Copper |

Insulation

| Element | Material | Nom. Thickness | Color Code |
|--------------|-------------------|--------------------|-------------------|
| Conductor(s) | PE - Polyethylene | 0.032 in (0.81 mm) | Black, Red, Clear |

Outer Shield

| Shield Type | Material | Coverage | Drainwire Type |
|-------------|-------------------------|----------|-------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 18 AWG (16x30) TC |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.031 in (0.79 mm) | 0.327 in (8.31 mm) |

Overall Cable Diameter (Nominal): 0.327 in (8.31 mm)

Electrical Characteristics

Electricals

| Element | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current |
|--------------|----------------------------|-------------------------------|---|------------------------------|
| Conductor(s) | 4.8 Ohm/1000ft (16 Ohm/km) | 26 pF/ft (85 pF/m) | 50 pF/ft (160 pF/m) | 7 Amps per Conductor at 25°C |

Voltage

| UL Voltage Rating |
|-----------------------------------|
| 600 V (UL AWM 20253), 300 V (CL3) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|---------------------|----------------|
| 80°C (UL AWM 20253) | -20°C to +80°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 3.3 in (84 mm) | 3.3 in (84 mm) |

Max. Pull Tension: 110 lbs

| | |
|--------------------|--------------------------|
| Bulk Cable Weight: | 60 lbs/1000ft (89 kg/km) |
|--------------------|--------------------------|

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Indoor |
| Sustainability: | CA Prop 65 |
| Flammability / Reaction to Fire: | UL1685 UL Loading, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 725, CL3 |
| AWM Compliance: | 20253 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.368 Revision Date: 12-15-2021 |
|----------------------|--|

Variants

| Item # | Color | Putup Type | Length | UPC |
|--------------|--------|------------|----------|--------------|
| 8618 060500 | Chrome | Reel | 500 ft | 612825213420 |
| 8618 060U500 | Chrome | UnReel | 500 ft | 612825213406 |
| 8618 0601000 | Chrome | Reel | 1,000 ft | 612825213413 |
| 8618 0605000 | Chrome | Reel | 5,000 ft | 612825213437 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#) [CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#) [CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [706/2R-BLACK-EACH](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-1000](#) [8125-CHR-100](#) [8164-CHR-1000](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#) [83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#)