



Product Description

Electronic, 3 Conductor 30AWG (7x38) Tinned Copper, PP Insulation, Overall Tinned Copper Braid(95%) Shield, PVC Outer Jacket

Technical Specifications

Product Overview

Suitable Appli	Suitable Applications: low voltage analog signa); low voltage control (24v,)	; line level audio; voice communicat	or
Construction Details							
onstructi	on Details						
Conductor							
Element	Number of Element	Size	Stranding	Material			
Conductor(s)	3	30 AWG	7x38	TC - Tinned Copper			
Insulation							
Element	Material	Nom. Thi	ckness	Color Code			
Conductor(s)	PP - Polypropylene	0.006 in (0	.15 mm) Bl	ack, Red, White			
Outer Shield							
Shield Type	Material	Coverage	Nc	otes			
Braid	Tinned Copper (TC)	95%	Paper Tap	e Separator			
Outer Jacket							
Separator	Material	Nom.	Thickness	Nom. Diameter			
Paper Tape	PVC - Polyvinyl Chlorid	de 0.014 i	n (0.36 mm)	0.096 in (2.4 mm)			
	Overall Cable Diameter (Nominal): 0.096 in (2.4 mm)						

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	98.5 Ohm/1000ft (323 Ohm/km)	25 pF/ft (82 pF/m)	43 pF/ft (140 pF/m)	0.9 Amps per Conductor at 25°C

Voltage

Voltage Rating 200 V

Mechanical Characteristics

Temperature

Operating -20°C to +105°C

Bend Radius

Stationary Min.Installation Min.1.0 in (25 mm)1.0 in (25 mm)

Max. Pull Tension:	22.5 lbs
Bulk Cable Weight:	8 lbs/1000ft (12 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor			
Sustainability:	CA Prop 65			
CPR Compliance:	CPR Euroclass: Eca			
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			

Product Notes

Notes:	Conductors cabled around textile strength member

History

Update and Revision:

Revision Number: 0.361 Revision Date: 12-15-2021

Variants

ltem #	Color	Putup Type	Length	UPC
8643 060100	Chrome	Reel	100 ft	612825213826
8643 060250	Chrome	Reel	250 ft	612825213833

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

8916-GRY-100 8917-BLK-100 8918-GRN/YEL-100 8920-BRN-1000 8920-RED-1000 89907-LT-DEC/GRY-500 CR3909-000 CR3927-000 01342.35T.01 01364.35T.01 CS2885-000 CS8782-000 CS9912-000 6200UE-NAT-U1000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 6304FE-877-U500 6309UE-877-1000 6320UE-NAT-U1000 644833-000 6502FE 8771000 6504UE-877-U1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 730859-000 MCC-USB-4-250 752687-000 768146-000 773159-000 7934A-BLK-1000 8125-CHR-100 8164-CHR-1000 820457-000 8205-CHR-1000 8240-BLK-U1000 82723-NAT-1000 82907-NAT-500 83003-YEL-500 83005-WHT-500 83006-DK-GRN-100 83008-WHT-1000 83009-BLK-100 83009-VIO-100