



Product: <u>8677</u> ☑

Electronic, 2 C #16 Str BC, PVC Ins

😭 Request Sample

# **Product Description**

Electronic, 2 Conductor 16AWG (19x28) Bare Copper, PVC Insulation

# **Technical Specifications**

# **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio

**Physical Characteristics (Overall)** 

# Conductor

AWG	Stranding	Material	No. of Conductors
16	19x29	BC - Bare Copper	2
Condu	uctor Count:		2

### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.024 in

# Color Chart

Number	Color
1	Brown
2	Red

## **Outer Shield Material**

Material No Shield

### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.149 x 0.254 in	0.022 in

# **Electrical Characteristics**

Electrical Characteristics	
Current	
Max. Recommended Current [A]	
6.5 Amps per Conductor at 25°C	
Voltage	
Non-UL Voltage Rating	
300 V RMS	
Temperature Range	
UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C
t	

## **Mechanical Characteristics**

Bulk Cable Weight:	33 lbs/1000ft
Max. Pull Tension:	60.8 lbs
Min Bend Radius/Minor Axis:	1.5 in

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
MII Order #39 (China RoHS):	Yes

#### Plenum/Non-Plenum

Plenum (Y	/////	

### **Part Number**

# Variants Item # Color Putup Type Length UPC 8677 060500 Chrome Reel 500 ft 612825214038 Footnote: C - CRATE REEL PUT-UP. History Lupdate and Revision: Revision Number: 0.290 Revision Date: 06-24-2020

#### © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

No

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005

 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA 

 0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 773159-000

 82841-877-5000
 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469

 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-100
 8769-060-1000
 8775-060 

 500
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444

 060U1000
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444