



# Product: <u>8691</u> ☑

# Electronic, 6 Pr #18 Str TC, PVC Ins, PVC Jkt, CMG

😭 Request Sample

# **Product Description**

Electronic, 6 Pair 18AWG (16x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

## **Technical Specifications**

### **Product Overview**

Suitable	Applications:	plications: low voltage analog signals (4-20ma, 0-10v,); low voltage digital control (24v,); line level audio; computer			
Construction Details					
Conductor					
Element	Number of Element	AWG	Stranding	Material	
Pair(s)	6	18	16x30	TC - Tinned Copper	
Insulation					
Element	Material	Т	hickness [in.]	1	Color Code
Pair(s)	PVC - Polyvinyl Chlori	ide 0.	013	Black & Red, Black	& White, Black & Green, Black & Blue, Black & Yellow, Black & Brown

	Material	Thickness	Nom. Diameter
	PVC - Polyvinyl Chloride	0.032 in	0.433 in
Cable Diameter (Nominal): 0.433 in			

#### **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	5.86 Ohm/1000ft	25.5 pF/ft	3.4 Amps per Conductor at 20°C

#### Voltage

UL Voltage Rating
300 V (CMG), 300 V (UL AWM 2464)

## **Mechanical Characteristics**

#### Temperature

UL Rating	Operating
80°C (UL AWM 2464)	-20°C to +80°C

#### Bend Radius

Stationary Min.	Installation Min.
.5 in	4.3 in
Max. Pull Tensio	
Max. Pull Tensio	n: 2
Bulk Cable Weig	ht: 1

**Standards and Compliance** 

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMG
AWM Compliance:	2464
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
History	

Update and Revision: Revision Number: 0.334 Revision Date: 08-12-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005

 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA 

 0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 773159-000

 82841-877-5000
 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469

 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-100
 8769-060-1000
 8775-060 

 500
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444

 060U1000
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444