



## **Product Description**

Electronic, 2 Conductor 18AWG (16x30) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

## **Technical Specifications**

## **Product Overview**

Construction			Suitable Applications: low voltage analog signals (4-20ma, 0-10		
Sonstruction	n Details				
Conductor					
Element Numb	per of Element AWG	Stranding	Material		
Pair(s) 1	18	16x30	TC - Tinned Copper		

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC

#### Outer Jacket Material

	Material	Thickness	Nom. Diameter
P٧	VC - Polyvinyl Chloride	0.028 in	0.222 in
Ca	Cable Diameter (Nominal): 0.222 in		

## **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	6.5 Ohm/1000ft	27.2 pF/ft	7.2 Amps per Conductor at 25°C

# Voltage

UL Voltage Rating 300 V (CM), 300 V (UL AWM 2092))

## **Mechanical Characteristics**

Temperature	
UL Rating	Operating
60°C (UL AWM 2092)	-20°C to +60°C
Bend Radius	
Stationary Min. Inst	tallation Min.
2.25 in 2.2	in
Max. Pull Tension:	54 lt

Bulk Cable Weight:

25 lbs/1000ft

**Standards and Compliance** 

Environmental Suitability:	Indoor
Flammability / Fire Resistance:	UL1685 UL Loading, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CM
AWM Compliance:	2092
CEC / C(UL) Compliance:	CM
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
Plenum Number:	88760, 87760 or 82760

#### **History**

Update and Revision: Revision Number: 0.377 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005
 6502FE

 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA-0078-22 

 4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 82841-877-5000

 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469
 060100
 8628-060 

 500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-1000
 8769-060-1000
 8775-060-500
 877541-000
 8780-060-1000

 88444-002-1000
 9159-060-500
 939870-000
 9423
 060U500
 9444
 060U1000
 9497
 0001000
 9515-060-1000
 9520-060-1000
 9524-060-1000

 9546-060-500

 9444
 060U1000
 9497
 0001000
 9515-060-1000
 9524-060-1000