

88112 Multi-Conductor - Low Cap. Computer Cable for EIA RS-232/422/485 Applications



For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (7x32) tinned copper conductors, plenum, foam FEP insulation, twisted pairs, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain wire, fluorocopolymer jacket.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | # Pairs | AWG | Stranding | Conductor Material |
|--------------|---------|-----|-----------|--------------------|
| 1 | 12 | 24 | 7x32 | TC - Tinned Copper |

Total Number of Conductors: 25

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|--|---------------------|
| FFEP - Foam Fluorinated Ethylene Propylene | 0.381 |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | 7x32 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (mm) |
|------------------------|--------------------------|
| PVDF - Fluorocopolymer | 0.356 |

Overall Cable

Overall Nominal Diameter: 10.084 mm

Pair

Pair Color Code Chart:

| Number | Color |
|------------------|-----------------------------|
| 1 | White/Blue & Blue/White |
| 2 | White/Orange & Orange/White |
| 3 | White/Green & Green/White |
| 4 | White/Brown & Brown/White |
| 5 | White/Gray & Gray/White |
| 6 | Red/Blue & Blue/Red |
| 7 | Red/Orange & Orange/Red |
| 8 | Red/Green & Green/Red |
| 9 | Red/Brown & Brown/Red |
| 10 | Red/Gray & Gray/Red |
| 11 | Black/Blue & Blue/Black |
| 12 | Black/Orange & Orange/Black |
| Single Conductor | White |

88112 Multi-Conductor - Low Cap. Computer Cable for EIA RS-232/422/485 Applications

Mechanical Characteristics (Overall)

| | |
|-----------------------------------|-----------------|
| Operating Temperature Range: | -20°C To +150°C |
| Bulk Cable Weight: | 130.962 Kg/Km |
| Max. Recommended Pulling Tension: | 609.403 N |
| Min. Bend Radius/Minor Axis: | 101.600 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|------------|
| NEC/(UL) Specification: | CMP |
| CEC/C(UL) Specification: | CMP |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flame Test

| | |
|-----------------|----------|
| UL Flame Test: | NFPA 262 |
| CSA Flame Test: | FT6 |

Plenum/Non-Plenum

| | |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

100

Nom. Inductance:

Inductance (µH/m)

0.68901

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

42.653

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

76.4473

Nominal Velocity of Propagation:

VP (%)

78

Nominal Delay:

Delay (ns/m)

4.2653

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

78.744

METRIC MEASUREMENT VERSION

88112 Multi-Conductor - Low Cap. Computer Cable for EIA RS-232/422/485 Applications

Nominal Outer Shield DC Resistance:

| |
|----------------------------|
| DCR @ 20°C (Ohm/km) |
| 38.7158 |

Max. Operating Voltage - UL:

| |
|----------------|
| Voltage |
| 300 V RMS |

Max. Recommended Current:

| |
|-------------------------------|
| Current |
| 1.1 Amps per conductor @ 25°C |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|-------|-------|--------------------------|
| 88112 0081000 | 1,000 FT | 97.000 LB | GRAY | C | 12#24 PR + 1#24 FS SOLEF |
| 88112 008500 | 500 FT | 48.000 LB | GRAY | C | 12#24 PR + 1#24 FS SOLEF |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 11-22-2013

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8917-GRN/YEL-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#)
[CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#)
[CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#)
[CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#)
[CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-](#)
[1000](#) [8125-CHR-100](#) [8164-CHR-1000](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#)
[83005-WHT-500](#) [83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#)