Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

8816 Hook-up/Lead - Hook-Up Wire on Racks (Kits)

For more Information please call

1-800-Belden1



General Description:

Picture

Not Available

Great for R and D labs, engineers, servicemen and hobbyists. Specify Part No. 8800 for Rack only.

Physical Characteristics (Overall)	
Physical Characteristics (Overall) Conductor	
AWG:	
AWG Stranding Conductor Material	
18 16x30 TC - Tinned Copper	
Insulation	
Insulation Material:	
Insulation Material	
PVC - Polyvinyl Chloride	
Overall Insulation	
Mechanical Characteristics (Overall)	
Operating Temperature Range:	80°C
Applicable Specifications and Agency Complia	ance (Overall)
Applicable Standards & Environmental Programs	
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Plenum/Non-Plenum	
Plenum (Y/N):	No
Notes (Overall)	
Notes: 8 Spools of 8522 in the following colors 1, 2, 3, 4, 5,	6, 9, 10 - Spool Lengths 25 Ft.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8816	1 EA	1.373 LB			18 STR PVC 8 COLOR KIT 1

Revision Number: 1 Revision Date: 05-14-2007

© 2016 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this product becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 01776.38.01
 M22759/16-14-5-500FT
 7046-BLACK-100
 7053-RED-1000
 F25935-000
 F60898-000

 82A0811-4-9-G110
 83004-ORG-1000
 83004-YEL-100
 83005-LT-BLU-1000
 83025-VIO-1000
 8524-WHT-100
 8525-ORG-1000
 8530

 BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 138498-000
 BFWUL3239-24-PINK
 C2016A.12.05
 C2016A.12.07

 C2065A.12.02
 8916-GRY-500
 8918-RED-100
 8919-DK-BLU-1000
 8919-YEL-100
 8920-YEL-100
 9242833001
 933205-000
 282257-000

 2841/7-YELLOW-1000
 2842/7-ORANGE-100
 2842/7-RED-1000
 2843/19-BLUE-100
 2843/1-YELLOW-100
 2844/7-BLACK-1000
 2855/1

 BLACK-100
 2855/1-BROWN-1000
 285750-010
 956299-4
 961473-000
 298-SILVER-100
 3047-YELLOW-100
 3048-YELLOW-1000
 3049-YELLOW-1000
 3049-YELLOW-1000