



**Product:** <u>8908</u> ☑

Lead Wire, #8 Str TC, PVC Ins, AWM 1028 AWM 1015 AWM 1231

# Request Sample

# **Product Description**

Low Temp Plastic Lead Wire, 8AWG (133x29) Tinned Copper, PVC Insulation, AWM 1028 AWM 1015 AWM 1231 CSA TYPE TEW 600V 105C

## **Technical Specifications**

## **Product Overview**

Suitable Applications: inter-connection circuits, internal wiring of computer and electronic equipments, internal wiring of appliances, machine tool wire

# **Physical Characteristics (Overall)**

#### Conductor

| AWG   | Stranding    | Material           | No. of Conductors |
|-------|--------------|--------------------|-------------------|
| 8     | 133x29       | TC - Tinned Copper | 1                 |
| Condu | uctor Count: |                    | 1                 |

#### Insulation

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.262 in         | 0.048 in               |

## **Electrical Characteristics**

## Voltage

UL Voltage Rating 600 V RMS

## **Temperature Range**

| Non-UL Temp Rating: | 105°C |
|---------------------|-------|
| UL Temp Rating:     | 105°C |

## **Mechanical Characteristics**

| Bulk Cable Weight: 74 lbs/1000ft |
|----------------------------------|
|----------------------------------|

#### **Standards**

| NEC Articles:            | Article 310                    |
|--------------------------|--------------------------------|
| NEC/(UL) Compliance:     | MTW or TW                      |
| UL AWM Style Compliance: | UL AWM Styles 1015, 1028, 1231 |
| CSA Rating:              | 600 V, 105°C                   |
| CSA AWM Compliance:      | CSA AWM I A/B                  |
| CSA Type:                | TEW or AWM I A/B               |

# **Applicable Environmental and Other Programs**

| EU Directive 2000/53/EC (ELV):     | Yes |
|------------------------------------|-----|
| EU Directive 2003/96/EC (BFR):     | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE):    | Yes |

| EU Directive 2015/863/EU:             | Yes                           |
|---------------------------------------|-------------------------------|
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-07-01                    |
| CA Prop 65:                           | Yes                           |
| MII Order #39 (China RoHS):           | Yes                           |

## Flammability, LS0H, Toxicity Testing

| UL Flammability:   | WW-1      |
|--------------------|-----------|
| UL voltage rating: | 600 V RMS |

#### Plenum/Non-Plenum

| Plenum (Y/N): | No |  |
|---------------|----|--|

#### **Part Number**

#### Variants

| Item #       | Color       | Putup Type | Length  | UPC          |
|--------------|-------------|------------|---------|--------------|
| 8908 010250  | Black       | Reel       | 250 ft  | 612825217992 |
| 8908 0101500 | Black       | Reel       | 1,500 m | 612825217985 |
| 8908 013250  | Blue, Dark  | Reel       | 250 ft  | 612825218005 |
| 8908 001250  | Brown       | Reel       | 250 ft  | 612825217831 |
| 8908 0081500 | Gray        | Reel       | 1,500 m | 612825217930 |
| 8908 005250  | Green, Dark | Reel       | 250 ft  | 612825217916 |
| 8908 002250  | Red         | Reel       | 250 ft  | 612825217886 |
| 8908 0071500 | Violet      | Reel       | 1,500 m | 612825217923 |
| 8908 004250  | Yellow      | Reel       | 250 ft  | 612825217909 |
| 8908 0041500 | Yellow      | Reel       | 1,500 m | 612825217893 |

Footnote: C - CRATE REEL PUT-UP

#### **History**

| Update and Revision: | Revision Number: 0.290 Revision Date: 07-26-2020 |
|----------------------|--|

### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000
BFWUL3239-24-PINK 22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 284711-000 961473-000 30802-009-250 30808-010-500
30810-010-500 99M0111-20-2 A00594-000 190571-000 22759/41-12-9CS2620 22759/41-16-9CS2620 22759/43-10-9CS2873 265925-000
CM9524-000 CMC-0553-1-9 31510-010-250 31514-009-500 32412-009-500 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007
400R0111-10-9 431660-000 ATFC0311-20-0 ATFC0311-20-3 44/7024-26-9-9 44A0112-22-9CS3184 456157-000 BFW-UL3239-24WHITE 55/0312-26-6L-CS2570 55A0811-12-9 55A6087-20-9-9-9 55A6315-22-9-9CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5
55PC0211-20-5CS2502 55PC0811-6-9CS2637 55PC1211-22-9-9CS3278