

Product: <u>9223</u> ☑ Audio Coax, Low Noise, 22 AWG Str TC, Foil + 95% TC Brd, PVC Jkt

Product Description

Audio Coax, Low Noise, 22 AWG (7x30) Tinned Copper Conductor, Inner PE Conductive Layer, PE Insulation, Duobond® II + 95% Tinned Copper Braid Shield, PVC Jacket

Technical Specifications

Product Overview

Suitable Applications: Low noise microphone, Analog audio, Instrumentation

Construction Details

Conductor

Size	Stranding	Nom. Diameter	Material
22 AWG	7x30	0.029 in	TC - Tinned Copper

Insulation

	Material	Nom. Insulation Diameter	
	PE - Polyethylene (Conductive)	0.036 in (0.91 mm)	
	PE - Polyethylene	0.112 in (2.84 mm)	

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Таре	Tri-Laminate (Alum+Poly+Alum)	Duobond® II	100%
2	Braid	Tinned Copper (TC)		95%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	e 0.195 in (4.95 mm)
Overall Cable Diameter (Nominal): 0.195 in	

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield
15.1 Ohm/1000ft (49.5 Ohm/km)	3.8 Ohm/1000ft (12 Ohm/km)	37 pF/ft (120 pF/m)
Electrical Characteristics Notes:	NBS Low Noise Test (Modifi	ied), MIL-C-17 Paragraph 4.8.14, 8 mV

Mechanical Characteristics

Temperature

Operating -35°C to +75°C

Bend Radius

Installation Min.

2 in

Max. Pull Tension:	8.85 lbs (4.01 kg)
Bulk Cable Weight:	24 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor	
Sustainability:	CA Prop 65	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

Product Notes

Notes:

Not recommended for RF use

History

Update and Revision:

Revision Number: 0.276 Revision Date: 12-15-2021

Variants

Item #	Color	Putup Type	Length	UPC
9223 010100	Black	Reel	100 ft	612825358831
9223 010500	Black	Reel	500 ft	612825357742
9223 0101000	Black	Reel	1,000 ft	612825357759

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Coaxial Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89880-003-1000
 CY2389-000
 8221-010-U1000
 9116-010-U500
 1322R-010-1000
 1807A-B59-U1000
 2020K8421-9X-CS3417
 9251-010

 1000
 9275-010-U1000
 935240-000
 980704-001
 CF2823-000
 33312-010-500
 CZ1589-000
 5022W0809-0CS3263
 10610-4-4
 EF8108-000

 1673B
 TIN100
 672525-001
 144517-000
 735A1-008-1000
 134655-000
 8212-010-U500
 480414-000
 7915A
 009U1000
 5024A1311-0

 1281S5
 010250
 1530A
 010U1000
 9248
 010U1000
 7809WB
 010500
 9244
 0101000
 1694A
 0081000
 1190A
 0101000
 8241F
 J5C1000

 1674A
 TIN50
 7915A
 0091000
 TRCH-50-2
 9066
 0031000
 7805R
 008100
 1674A
 TIN100
 9116SB
 0101000
 9271
 0061000
 1613A
 0101000

 1807A
 B591000
 5339Q5
 009U500
 539945
 0091000
 9116R
 0101000
 8207
 0101000
 8241A
 0101000