



REPRESENTATIVE IMAGE

Product: [9250](#)

95Ω Twinax RG-22B/U Type, 1Pr #18 Str BC, PE Ins, PE Inner Jkt, Two TC Braids, Non-contaminating PVC Jkt

Product Description

Twinax 95Ω RG-22B/U Type, 1 Pair, 18 AWG (7x26) bare copper, polyethylene insulation, polyethylene inner jacket, tinned copper double braid shield (95% coverage each), non-contaminating PVC jacket

Technical Specifications

Product Overview

Suitable Applications:	Computer, Instrumentation
------------------------	---------------------------

Construction Details

RG Type:	22
----------	----

Conductor

Size	Stranding	Nom. Diameter	Material	Notes
18 AWG	7x26	0.046 in	BC - Bare Copper	
18 AWG	7x26	0.046 in	BC+TC - Bare Copper + Tinned Copper	Only center strand is Tinned

Insulation

Material	Nom. Insulation Diameter	Color Code	Notes
PE - Polyethylene	0.089 in (2.3 mm)	Clear	PE on both conductors
PE - Polyethylene	0.282 in (7.16 mm)	Clear	PE over pair

Outer Shield

Layer	Outer Shield Type	Material	Coverage
1	Braid	Tinned Copper (TC)	95%
2	Braid	Tinned Copper (TC)	95%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride (Non-Contaminating)	0.416 in (10.6 mm)

Overall Cable Diameter (Nominal):	0.416 in (10.6 mm)
-----------------------------------	--------------------

Electrical Characteristics

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.30 dB/100ft
10 MHz	0.90 dB/100ft
20 MHz	1.30 dB/100ft
50 MHz	2.10 dB/100ft
100 MHz	3.00 dB/100ft
200 MHz	4.50 dB/100ft
400 MHz	6.30 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Cond (Mutual)	Nom. Characteristic Impedance	Nom. Velocity of Prop.
--------------------	-----------------------	--	-------------------------------	------------------------

6.6 Ohm/1000ft (22 Ohm/km)	0.9 Ohm/1000ft (3.0 Ohm/km)	16.0 pF/ft (52.5 pF/m)	95 Ohm	66%
----------------------------	-----------------------------	------------------------	--------	-----

Transfer Impedance

Max. Transfer Impedance
0.7 mOhm/m
1.0 mOhm/m
7.0 mOhm/m

Voltage

Voltage Rating
750 V

Mechanical Characteristics

Temperature

Operating
-40°C to +60°C

Bend Radius

Installation Min.
4.5 in (110 mm)

Max. Pull Tension:	237 lbs (108 kg)
Bulk Cable Weight:	113 lbs/1000ft (168 kg/km)

Standards and Compliance

Environmental Suitability:	Outdoor, Outdoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	VW-1
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.390 Revision Date: 12-15-2021
----------------------	--

Variants

Item #	Color	Putup Type	Length	UPC
9250 010500	Black	Reel	500 ft	612825225751
9250 0101000	Black	Reel	1,000 ft	612825225744

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [CY2389-000](#) [8221-010-U1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [735A1-008-1000](#) [8212-010-U500](#) [480414-000](#) [7915A 009U1000](#) [5024A1311-0](#) [1281S5 010250](#) [1530A 010U1000](#) [9248 010U1000](#) [9244 0101000](#) [1694A 0081000](#) [1190A 0101000](#) [8241F J5C1000](#) [1674A TIN50](#) [7915A 0091000](#) [TRCH-50-2](#) [9066 0031000](#) [7805R 008100](#) [1674A TIN100](#) [9116SB 0101000](#) [9271 0061000](#) [1613A 0101000](#) [1807A B591000](#) [5339Q5 009U500](#) [539945 0091000](#) [9116R 0101000](#) [89207 010100](#) [9058 0101000](#) [8241A 0101000](#) [DA7805R 0101000](#) [C6424](#)