

Product: <u>9397</u> ☑





Product Description

24 AWG stranded (105x44) high-conductivity bare copper conductors, PVC insulation, double bare copper spiral shield (95% coverage), PVC jacket.

Technical Specifications

Pilysi	Physical Characteristics (Overall)							
Conductor								
AWG	Stranding		Materia	ı		Nominal Dian	neter	No. of Conductor
24	105x44	BC -	Bare Copper (Hig	gh Co	onductivity)	0.024 in		2
Condu	Conductor Count: 2			2				
nsulati	ion							
	Material		Nominal Diame	eter	Nominal W	/all Thickness	1	
PVC -	Polyvinyl Ch	loride	0.048 in		0.012 in			
0 : 1	Туре		Material		verage [%]			
Spiral	Type Serve / Scree	en Ba	Material are Copper (BC)					
•								
•	Serve / Scree			95%	%	/all Thickness	1	
Outer J	Serve / Scree	rial	are Copper (BC) Nominal Diame	95%	%	/all Thickness		
Outer J	Serve / Screen Jacket Mater Material Polyvinyl Ch	rial loride	Nominal Diame	95%	% Nominal W	/all Thickness		
Outer J	Serve / Scree Jacket Mater Material	rial loride	Nominal Diame	95%	% Nominal W	/all Thickness		
Outer J PVC -	Serve / Screen Jacket Mater Material Polyvinyl Ch	rial loride	Nominal Diame	95%	% Nominal W	/all Thickness		
Outer J PVC - Electi	Serve / Scree Jacket Mater Material Polyvinyl Ch rical Chal	rial loride	Nominal Diame	95%	Mominal W 0.031 in			I

Capacitance

Nom. Capacitance Conductor to Conductor		Nom. Capacitance Conductor to Other Conductor to Shield
47.	.3 pF/ft	110 pF/ft

Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance
47 Ohm

Current

Max. Recommended Current [A] 3.36 Amps per Conductor at 25°C

Voltage



Temperature Range

Non-UL Temp Rating:	80°C
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	22 lbs/1000ft
Max. Pull Tension:	10 lbs
Min Bend Radius/Minor Axis:	1.75 in

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Suitability

Plenum/Non-Plenum

Ple	enum (Y/N):	No	

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
9397 B59500	Black, Matte	Reel	500 ft	612825239949
9397 B591000	Black, Matte	Reel	1,000 ft	612825239932
Footnote:			С	- CRATE REEL I

History

Update and Revision:	Revision Number: 0.295 Revision Date: 06-24-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

89182-010-1000 89705-008-500 89842-002-1000 6000FE-877-1000 6120UL-002-1000 CS2885-000 M27500-20SP2S23 6300FE-877-U1000 6309UE-877-1000 M3905-BK005 6502FE 8771000 6541PA-008-U1000 CV6807-000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 752687-000 768146-000 773159-000 82841-877-5000 83318E-009-500 8348-060-500 83559-002-1000 83653-002-5000 83659-002-1000 83709-002-1000 8404-060-500 8469 060100 858171-000 8628-060-500 868361-001 8730-060-1000 8737-060-U1000 8747-060-100 8747-060-1000 8769-060-1000 8775-060-500 8780-060-1000 8782-001-U1000 88444-002-1000 9159-060-500 9318-060-1000 939870-000 9423 060U500