

Product: <u>9397</u> ☑

Microphone Cable, 2 Conductor 24 AWG, BC



Product Description

24 AWG stranded (105x44) high-conductivity bare copper conductors, PVC insulation, double bare copper spiral shield (95% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

sonuu	ctor							
AWG	Stranding		Materia	I		Nominal Diam	eter N	o. of Conductors
24	105x44	BC - I	Bare Copper (Hig	gh C	onductivity)	0.024 in	2	
Condu	uctor Count:				2			
nsulat	tion							
	Material		Nominal Diame	eter	Nominal W	/all Thickness		
PVC -	Polyvinyl Chl	oride	0.048 in		0.012 in			
Outer \$	Shield							
	Туре		Material	Со	verage [%]			
Spiral	Serve / Scree	n Ba	are Copper (BC)	95	%			
	Material		Nominal Diame	eter		all Thickness		
PVC -	Polyvinyl Chl	oride	0.176 in		0.031 in			
		acte	eristics					
Condu	ctor DCR							
Condu Nomi	ctor DCR nal Conducto		R Nominal Con		tor DCR Co	nductor Resist	ance	
Condu Nomi	ctor DCR		R Nominal Con 24.6 Ohm/100		tor DCR Co	nductor Resist	ance	
Condu Nomi	ctor DCR nal Conducto Dhm/1000ft				tor DCR Co	nductor Resist	ance	
Condu Nomi 24.6 C Capaci	ctor DCR nal Conducto Dhm/1000ft itance Nom. Capacit	r DCf	24.6 Ohm/100					Other Conductor to

Nominal Inductanc

0.19 µH/ft

Impedance

Nominal Characteristic Impedance 47 Ohm

Current

Max. Recommended Current [A] 3.36 Amps per Conductor at 25°C

Non-UL Voltage Rating

300 V RMS

Temperature Range

Non-UL Temp Rating:	2°08
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	22 lbs/1000ft
Max. Pull Tension:	10 lbs
Min. Bend Radius/Minor Axis:	1.75 in

Applicable Environmental and Other Programs

Environmental Space:Indoor (Not Riser or Plenum)EU Directive 2000/53/EC (ELV):YesEU Directive 2003/11/EC (BFR):YesEU Directive 2011/65/EU (RoHS 2):YesEU Directive 2012/19/EU (WEEE):YesEU Directive 2015/863/EU (RoHS 2 amendment):YesEU Directive Compliance:EU Directive 2003/11/EC (BFR)EU CE Mark:YesMII Order #39 (China RoHS):Yes		
EU Directive 2003/11/EC (BFR): Yes EU Directive 2011/65/EU (RoHS 2): Yes EU Directive 2012/19/EU (WEEE): Yes EU Directive 2015/863/EU (RoHS 2 amendment): Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes	Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2011/65/EU (RoHS 2): Yes EU Directive 2012/19/EU (WEEE): Yes EU Directive 2015/863/EU (RoHS 2 amendment): Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes	EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2012/19/EU (WEEE): Yes EU Directive 2015/863/EU (RoHS 2 amendment): Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes	EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment): Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes	EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes	EU Directive 2012/19/EU (WEEE):	Yes
EU CE Mark: Yes	EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
	EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
MII Order #39 (China RoHS): Yes	EU CE Mark:	Yes
	MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes

No

Plenum/Non-Plenum

Plenum	(Y/N)):

Part Number

Variants

Item #	Color	Put-Up Type	Length	UPC
9397 B59500	Black, Matte	Reel	500 ft	612825239949
9397 B591000	Black, Matte	Reel	1,000 ft	612825239932
Footnote:				C - CRATE REE

History

Update and Revision:

Revision Number: 0.372 Revision Date: 12-15-2021

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

8916-GRY-100 8917-BLK-100 8918-GRN/YEL-100 8920-BRN-1000 8920-RED-1000 89907-LT-DEC/GRY-500 CR3909-000 CR3927-000 01342.35T.01 01364.35T.01 CS2885-000 CS8782-000 CS9912-000 6200UE-NAT-U1000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 6304FE-877-U500 6309UE-877-1000 6320UE-NAT-U1000 644833-000 6502FE 8771000 6504UE-877-U1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 730859-000 MCC-USB-4-250 752687-000 768146-000 773159-000 7934A-BLK-1000 8125-CHR-100 8164-CHR-1000 820457-000 8205-CHR-1000 8240-BLK-U1000 82723-NAT-1000 82907-NAT-500 83003-YEL-500 83005-WHT-500 83006-DK-GRN-100 83008-WHT-1000 83009-BLK-100 83009-VIO-100