



Product Description

High Performance Instrumentation, 1 Pair 16AWG (19x29) Tinned Copper, PVC Insulation E2 Color Code, PVC Outer Jacket, PLTC-ER

Technical Specifications

Product Overview

Product Overview			
Suitable Applications: Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V			
Construction Details			
Conductor			
Element Number of Element Si	ize Stranding Material		
Pair(s) 1 16 A	AWG 19x29 TC - Tinned Copper		
Insulation			
Element Material	Nom. Thickness Nom. Insulation Diameter Color Code		
Pair(s) PVC - Polyvinyl Chloride	0.0185 in (0.470 mm) 0.096 in (2.4 mm) Black & Red		
Outer Jacket			
Material Nom. Thickness Nom. Diameter Ripcord			
PVC - Polyvinyl Chloride 0.037 in (0.94 mm) 0.260 in (6.60 mm) Yes			
Overall Cable Diameter (Nominal): 0	0.260 in (6.60 mm)		
Electrical Characteristics			
Electricals			
Element Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond		
Pair(s) 4.2 Ohm/1000ft (14 Ohm/km) 31 pF/ft (100 pF/m)			
Voltage UL Voltage Rating			
300 V (PLTC, CMG), 150 V (ITC)			
Mechanical Characteristics			
Temperature			
UL Temperature Operating			
105°C -30°C to +105°C			
Table Notes:	AWM 80°C		
Bend Radius			
Stationary Min. Installation Min.			
2.6 in (66 mm) 2.6 in (66 mm)			
	80 lbs 35 lbs/1000ft (52 kg/km)		
Dani Gabie Weigilt.	Jo inder room (oz nyimit)		

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance	
Flammability / Reaction to Fire:	UL1685 Vertical Tray Flame Test, FT4, T-29-520, 1202	
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC-ER, PLTC-ER	
AWM Compliance:	2464	
CEC / C(UL) Compliance:	CMG	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

History

Update and Revision: Revision Number: 0.454 Revision Date: 12-15-2021

Variants

Item #	Color	UPC
9410 0601000	Chrome	612825240211
9410 0602500	Chrome	612825240228
9410 060U1000	Chrome	612825240198
9410 060U500	Chrome	612825240204

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

8916-GRY-100 8917-BLK-100 8918-GRN/YEL-100 8920-BRN-1000 8920-RED-1000 89907-LT-DEC/GRY-500 CR3909-000 CR3927-000 01342.35T.01 01364.35T.01 003201-000 CS2885-000 CS8782-000 CS9912-000 6200UE-NAT-U1000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 6304FE-877-U500 6309UE-877-1000 6320UE-NAT-U1000 644833-000 6502FE 8771000 6504UE-877-U1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 706/2R-BLACK-EACH 720451-000 730859-000 MCC-USB-4-250 752687-000 768146-000 773159-000 7934A-BLK-1000 8125-CHR-100 8164-CHR-1000 820457-000 8205-CHR-1000 8240-BLK-U1000 82723-NAT-1000 82907-NAT-500 83003-YEL-500 83005-WHT-500 83006-DK-GRN-100 83008-WHT-1000