



Product: <u>9411</u> ☐

High Perform Instr, 1 Pr #14 Str TC, PVC Ins E2, PVC Jkt, PLTC-ER

Product Description

High Performance Instrumentation, 1 Pair 14AWG (42x30) Tinned Copper, PVC Insulation E2 Color Code, PVC Outer Jacket, PLTC-ER

Technical Specifications

Product Overview

Construction Details
Conductor
Element Number of Element AWG Stranding Material
Pair(s) 1 14 42x30 TC - Tinned Coppe
Insulation Element Material Thickness [in.] Color Code
Pair(s) PVC - Polyvinyl Chloride 0.022 Black, Red
Outer Jacket Material Material Thickness Nom. Diameter Ripcord
PVC - Polyvinyl Chloride 0.042 in 0.322 in Yes
Cable Diameter (Nominal): 0.322 in

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond
Pair(s)	2.6 Ohm/1000ft	27 pF/ft

Voltage

UL Voltage Rating 300 V (PLTC), 150 V (ITC)

Mechanical Characteristics

Temperature

UL Rating	Operating
105°C	-30°C to +105°C
Table Note	·s.

Bend Radius



Max. Pull Tension:	107 lbs
Bulk Cable Weight:	56

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance	
Flammability / Fire Resistance:	UL1666 Riser, FT4, T-29-520, 1202	
NEC / UL Compliance:	CL3R, ITC-ER, PLTC-ER	
AWM Compliance:	2464	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

History

Update and Revision:	Revision Number: 0.336 Revision Date: 07-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

89182-010-1000 6000FE-877-1000 M27500-20SP2S23 6300FE-877-U1000 6309UE-877-1000 6502FE 8771000 6541PA-008-U1000 CV6807-000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 752687-000 82841-877-5000 8348-060-500 83559-002-1000 83653-002-5000 83659-002-1000 83709-002-1000 8404-060-500 8469 060100 8628-060-500 868361-001 8730-060-1000 8737-060-U1000 8747-060-100 8747-060-1000 8747-060-1000 8769-060-1000 8775-060-500 877541-000 8780-060-1000 88444-002-1000 9159-060-500 939870-000 9423 060U500 9444 060U1000 9497 0001000 9515-060-1000 9520-060-1000 9524-060-1000 9546-060-500 9572-002-U500 9774-060-1000 1213F-D15-A1000 1213F-009-A1000