



Product: <u>9418</u>

Electronic, 4 C #18 Str TC, SRPVC Ins, OS, PVC Jkt, CMG

😭 Request Sample

Product Description

Electronic, 4 Conductor 18AWG (19x30) Tinned Copper, SRPVC Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMG

Technical Specifications

Product Overview

Construction Details Conductor Element Number of Element AWG Stranding Material Conductor(s) 4 18 19x30 TC - Tinned Copper Insulation Element Material Thickness [in.] Color Code Conductor(s) SR-PVC - Polyvinyl Chloride (Semi-Rigid) 0.011 Red, Green, Black, White Outer Shield Material Shield Type Material Coverage Drainwire Type Tape Bi-Laminate (Alum+Poly) 100% 20 AWG (19x32) TC Outer Jacket Material Material Thickness Nom. Diameter PVC - Polyvinyl Chloride 0.035 in 0.245 in	Suitable Appli	cations: lo	w voltar	ne analog si	nals (4-20ma 0-10v	(2): low voltage control (2)	4v,); line level audio; voice communications; panel wir
Element Number of Element AWG Stranding Material Conductor(s) 4 18 19x30 TC - Tinned Copper Insulation Image: Color Code Image: Color Code Image: Color Code Conductor(s) SR-PVC - Polyvinyl Chloride (Semi-Rigid) 0.011 Red, Green, Black, White Duter Shield Material Coverage Drainwire Type Tape Bi-Laminate (Alum+Poly) 100% 20 AWG (19x32) TC Outer Jacket Material Material Coverage Drainwire Type PVC - Polyvinyl Chloride 0.035 in 0.245 in	Ourable Applications. In www.iage analog signals (+2011a, 0-104,), tow volage control (244,), the revert addit, volce communications, parter withing						
ElementNumber of ElementAWGStrandingMaterialConductor(s)41819x30TC - Tinned CoppernsulationElementMaterialThickness [in.]Color CodeConductor(s)SR-PVC - Polyvinyl Chloride0.011Red, Green, Black, WhiteDuter Shield TypeMaterialCoverageDrainwire TypeTapeBi-Laminate (Alum+Poly)100%20 AWG (19x32) TCDuter Jacket MaterialMaterialThicknessMaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in	Constructi	on Details					
ElementNumber of ElementAWGStrandingMaterialConductor(s)41819x30TC - Tinned CopperInsulationElementMaterialThickness [in.]Color CodeConductor(s)SR-PVC - Polyvinyl Choride (Semi-Rigid)0.011Red, Green, Black, WhiteOuter Shield TypeMaterialCoverageDrainwire TypeTapeBi-Laminate (Alum+Poly)100%20 AWG (19x32) TCOuter Jacket HaterialThicknessNom. DiameterPVC - Polyvinyl Choride0.035 in0.245 in							
Conductor(s)41819x30TC - Tinned CopperInsulationElementMaterialThickness [in.]Color CodeConductor(s)SR-PVC - Polyvinyl C IUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUU	Conductor						
Insulation Element Material Thickness [in.] Color Code Conductor(s) SR-PVC - Polyvinyl Chloride (Semi-Rigid) 0.011 Red, Green, Black, White Outer Shield Material Shield Type Material Coverage Drainwire Type Tape Bi-Laminate (Alum+Poly) 100% 20 AWG (19x32) TC Outer Jacket Material Material Thickness Nom. Diameter PVC - Polyvinyl Chloride 0.035 in 0.245 in	Element	Number of Element	AWG	Stranding	Material		
ElementMaterialThickness [in.]Color CodeConductor(s)SR-PVC - Polyvinyl Chloride (Semi-Rigid)0.011Red, Green, Black, WhiteOuter Shield TypeShield TypeMaterialCoverageDrainwire TypeTapeBi-Laminate (Alum+Poly)100%20 AWG (19x32) TCOuter Jacket MaterialMaterialMaterialThicknessMaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in	Conductor(s)	4	18	19x30	TC - Tinned Coppe	er	
ElementMaterialThickness [in.]Color CodeConductor(s)SR-PVC - Polyvinyl Chloride (Semi-Rigid)0.011Red, Green, Black, WhiteOuter Shield MaterialShield TypeMaterialCoverageDrainwire TypeTapeBi-Laminate (Alum+Poly)100%20 AWG (19x32) TCOuter Jacket MaterialMaterialThicknessMaterialNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in							
Conductor(s) SR-PVC - Polyvinyl Chloride (Semi-Rigid) 0.011 Red, Green, Black, White Outer Shield Type Coverage Drainwire Type Shield Type Bi-Laminate (Alum+Poly) 100% 20 AWG (19x32) TC Outer Jacket Haterial Thickness Nom. Diameter PVC - Polyvinyl Thickness Nom. Diameter	Insulation						
Outer Shield Material Coverage Drainwire Type Shield Type Material Coverage Drainwire Type Tape Bi-Laminate (Alum+Poly) 100% 20 AWG (19x32) TC Outer Jacket Material Thickness Nom. Diameter PVC - Polyvinyl Chloride 0.035 in 0.245 in	Element	Mate	rial		Thickness [in.]	Color Code	
Shield TypeMaterialCoverageDrainwire TypeTapeBi-Laminate (Alum+Poly)100%20 AWG (19x32) TCOuter Jacket MaterialMaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in	Conductor(s)	SR-PVC - Polyvinyl C	hloride	(Semi-Rigio	i) 0.011	Red, Green, Black, White	
Shield TypeMaterialCoverageDrainwire TypeTapeBi-Laminate (Alum+Poly)100%20 AWG (19x32) TCOuter Jacket MaterialMaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in							1
Tape Bi-Laminate (Alum+Poly) 100% 20 AWG (19x32) TC Outer Jacket Material Nom. Diameter PVC - Polyviv // Chloride 0.035 in 0.245 in	Outer Shield N	laterial					
Outer Jacket Material Thickness Nom. Diameter PVC - Polyvinyl Chloride 0.035 in 0.245 in	Shield Type	Material	С	overage	Drainwire Type		
MaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in	Таре	Bi-Laminate (Alum+P	oly) 10	0% 2	0 AWG (19x32) TC		
MaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.035 in0.245 in							
PVC - Polyvinyl Chloride 0.035 in 0.245 in	Outer Jacket I	Material					
	Material Thickness Nom. Diameter						
	PVC - Polyvin	yl Chloride 0.035 in	0.24	5 in			
	Cable Diamet	or (Nominal):	245 in		4		
	Electrical (Characteristics					

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current		
Conductor(s)	6.5 Ohm/1000ft	40 pF/ft	pF/ft 72 pF/ft			
Nom Outer Shield DCR: 8		5 Ohm/1000ft				

Voltage

UL Voltage Rating 300 V (CMG), 300 V (UL AWM 2464)

Mechanical Characteristics

Temperature

UL Rating	Operating
80°C (UL AWM 2464)	-20°C to +80°C

Bend Radius

Stationary Min. Installation Min.

2.5 in	2.5 in	
Max. Pull Tensio	n:	100 lbs
Bulk Cable Weight:		42 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMG
AWM Compliance:	2464
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
Plenum Number:	89418 or 82418

History

Update and Revision: Revision Number: 0.359 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005

 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA

 0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 773159-000

 82841-877-5000
 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469

 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-100
 8769-060-1000
 8775-060

 500
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444

 060U1000
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444