



Product: <u>9451DP</u> ☑

Line Level Audio Cable, 2 Parallel Pr #22 Str TC, O/A Foil, Flamarrest® Jkt, CMP

Product Description

Line Level Audio Cable, 2 Parallel Pair 22 AWG (7 x 30) Tinned Copper, FEP insulation, Overall Beldfoil® Shield, Flamarrest® Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications: Line level audio; Low voltage				voltage analog signals and	
Constru	uction Details				
Conducto	r				
Element	Number of Element	AWG	Stranding	Material	
Pair(s)	2	22	7x30	TC - Tinned Co	opper
1					
Insulation					
Element	t Material			Thickness [in.]	Color Code
Pair(s)	FEP - Fluorinated Eth	ylene F	Propylene (0.008	Black & Red, Black & White
Outor Shi	eld Material				
				-	
Shield Ty		erage	Drainwire		
Таре	Alum / Poly 100	%	22 AWG (7	x30) TC	
Outer Jac	ket Material				
		iness	Nom, Diam	eter	
Material Thickness Nom. Diameter PVC - Polyvinyl Chloride 0.017 in 0.127 in					
Table Notes: Jacket and shield are bonde			bonded so both can be ren		
Cable Diameter (Nominal): .127 in			in		

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond		Nom. Capacitance Cond-to-Other (Conds + Shield)	Characteristic Impedence	Nom. Velocity of Prop.	Max. Current	
Pair(s)	14.1 Ohm/1000ft	35 pF/ft		67 pF/ft	42 Ohm 69%		2.9 Amps per conductor @ 25°C	
Nom Outer Shield DCR: 14.3 Ohm/1000ft			14.3 Ohm/1000ft					

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

UL Rating	Operating
60°C	-20°C to +75°C

Bend Radius

Stationary Min. Installation Min.	
2.5 in 1.3 in	
Max. Pull Tension:	54 lbs
Bulk Cable Weight:	24 lbs/1000ft

Environmental Suitability:	Indoor - Plenum, Indoor	
Flammability / Fire Resistance:	NFPA 262, UL 910 (Plenum), FT6	
NEC / UL Compliance:	Article 800, CMP	
CEC / C(UL) Compliance:	CMP	
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Non-Plenum Number:	9451D	

History

Update and Revision:

Revision Number: 0.305 Revision Date: 07-31-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005

 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA

 0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 773159-000

 82841-877-5000
 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469

 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-100
 8769-060-1000
 8775-060

 500
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444

 060U1000
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444