
	<b>TECHNICAL DATA SHEET</b>	code	<b>9506</b>
		version	<b>4</b>
		date	<b>2005-11-03</b>
	<b>9506</b>	page	<b>1/2</b>

## APPLICATION

Instrumentation and computer cable for EIA RS-232 data transmission applications.

## CONSTRUCTION




<b>1. Conductor</b>	AWG24 (7xAWG32) tinned Cu
<b>2. Insulation</b>	
Material	PVC
Diameter over insulation	1.12 ± 0.05 mm
Colour of insulation	Pair 1 (central): Black and red Pair 2: Black and white Pair 3: Black and green Pair 4: Black and blue Pair 5: Black and yellow Pair 6: Black and brown
<b>3. Foil (Beldfoil®)</b>	
Material	Aluminium / Polyester
Thickness	9 / 23 µm
<b>4. Drainwire</b>	AWG20 (7xAWG28) tinned Cu
<b>5. Sheath</b>	
Material	PVC
Colour	Chrome 060
Minimum wall thickness	0.61 mm
Minimum average wall thickness	0.762 mm
Nominal diameter over sheath	7.34 mm

## REQUIREMENTS AND TEST METHODS

### Electrical:

Nominal resistance conductor	78.7 Ω/km
Nominal resistance shield	52.5 Ω/km
Nominal capacitance conductor to conductor of a pair	98.4 pF/m
Nominal capacitance conductor to shield + other cond.	164.0 pF/m
Testvoltage conductor-conductor	2500 VDC, 3 seconds
Testvoltage conductor-screen	2500 VDC, 3 seconds
Voltage rating	300 V RMS
Maximum continuous current per conductor @ 25 °C	1.5 A

	<b>TECHNICAL DATA SHEET</b>	code	<b>9506</b>
		version	<b>4</b>
		date	<b>2005-11-03</b>
	<b>9506</b>	page	<b>2/2</b>

**Mechanical and physical:**

Flame resistance	UL FT4, CSA FT1
Applicable specification	UL type CMG, AWM 2464, CEC C(UL) CMG, AWM I/A
Temperature range processing and operating	-15 to +80 °C
Temperature range storage	-30 to +80 °C
Minimum bending radius	10 x cable diameter
Maximum pulling tension	300 N

\*Nominal values are for information only.

**MARKING**

Colour code 2852: chrome sheath with text ‘BELDEN V 9506 CMG 6PR24 SHIELDED (UL) E108998 OR AWM 2464 OR C(UL) CMG FT4---LL7874 CSA AWM I A 80C 300V FT1’

**PACKAGING**

On non-returnable reels with a length of 31 m (± 0%) or on non-returnable reels with a length of 153 m (± 0%) or on non-returnable reels with a length of 305 m (± 0%) or unreel package with a length of 153 m (± 0%) or unreel package with a length of 305 m (± 0%).

Each reel is labelled with the following data:

Belden Logo. Belden code number. Item description. Length on the reel. Date of manufacture. CE-marking.



Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Belden](#) manufacturer:*

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8917-GRN/YEL-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#)  
[CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#)  
[CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#)  
[CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#)  
[CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-](#)  
[1000](#) [8125-CHR-100](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#)  
[83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#) [83009-VIO-100](#)