



Product Description

High Performance Instrumentation, 3 Pair 22AWG (7x30) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC-ER

Technical Specifications

Product Overview

0.11.1.1	. 11 II			
Suitable Applications: Instrumentation,			n, Sensors, Valves, Po	
Constru	uction Detai	ls		
Conducto	r			
Element	Number of Ele	ment A	NG Stranding	Material
Pair(s)	3	22	7x30	TC - Tinned Copper
Insulation				
Element	Materia	1	Thickness [in.	Color Code
Pair(s)	PVC - Polyvinyl			Black, Red and Nur
1 an(3)	1 VO - I Olyvillyi	onionae	0.017	black, red and run
Outer Shie	eld Material			
Shield Ty	/pe Ma	terial	Coverage	Drainwire Type
Таре	Bi-Laminate	e (Alum+F	Poly) 100%	22 AWG (7x30) TC
	ket Material			
		Thickne		
PVC - Po	lyvinyl Chloride	0.042 in	0.327 in	Yes
Cable Diameter (Nominal): 0.327 in				

Electrical Characteristics

Electricals	

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current	
Pair(s)	15.0 Ohm/1000ft	26 pF/ft	45 pF/ft	3.4 Amps per Conductor at 25°C	
Nom Outer Shield DCR:		15 Ohm/1000ft			

Voltage

UL Voltage Rating

300 V (PLTC, CMG), 150 V (ITC)

Mechanical Characteristics

Temperature	•	
UL Rating	Operating	
105°C -	-30°C to +105°C	
Table Notes:	:	

Bend Radius

Stationary Min.	Installation Min.
3.3 in	3.3 in
Max. Pull Tension:	
Bulk Cable Weight:	

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial
Flammability / Fire Resistance:	UL1685 UL Loading, FT4, T-29-520, 1202
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC-ER, PLTC-ER
AWM Compliance:	2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.369 Revision Date: 09-03-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 89842-002-1000
 6000FE-877-1000
 6120UL-002-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877

 U1000
 6309UE-877-1000
 M3905-BK005
 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4

 9CS2973
 CXA-0078-16-1-9CS2405
 CXA-0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000

 720451-000
 752687-000
 768146-000
 773159-000
 82841-877-5000
 83318E-009-500
 8348-060-500
 83653-002-5000

 83659-002-1000
 83709-002-1000
 8404-060-500
 8469
 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000

 8747-060-100
 8747-060-1000
 8769-060-1000
 8775-060-500
 8780-060-1000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060

 1000
 939870-000
 9423
 060U500
 8775-060-500
 8780-060-1000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060