



Product Description

Electronic, 3 Conductor 22AWG (7x30) Tinned Copper, PP Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

Technical Specifications

Product Overview

			Product Overview				
Suitable Applications: low vol		voltag	e analog sig	gnals (4-20ma, 0-10v,); low voltage control (24v,); line level audio; voice communications; pa	
Constructi	on Details						
Conductor							
Element	Number of E	lement /	AWG	Stranding	Material		
Conductor(s)	3	2	22	7x30	TC - Tinned Copper		
nsulation						a.	
Element	Materia	I TI	nickne	ess [in.]	Color Code		
Conductor(s)	PP - Polyprop	oylene 0.	009	BI	lack, Red, White		
Outer Shield N	laterial						
Shield Type	Material (Coverage	Dr	ainwire Ty	ре		
Таре	Alum / Poly	100%	22 A	WG (19x34) TC		
Outer Jacket I	Aaterial						
Mater	ial Tł	nickness	Nom	. Diameter			
PVC - Polyvin	yl Chloride 0.	020 in	0.145	5 in			
Cable Diameter (Nominal): 0.145 in							

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	16 Ohm/1000ft	32 pF/ft	60 pF/ft	3 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V (CM)

Mechanical Characteristics

Temperature

Operating
-20°C to +90°C

Bend Radius

Stationary Min.	Installation Min.
1.5 in	1.5 in

Max. Pull Tension:	29 lbs	
Bulk Cable Weight:	16 lbs/1000ft	

Standards and Compliance

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 UL Loading, FT1, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CM
CEC / C(UL) Compliance:	СМ
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision: Revision Number: 0.341 Revision Date: 07-31-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 89842-002-1000
 6000FE-877-1000
 6120UL-002-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877

 U1000
 6309UE-877-1000
 M3905-BK005
 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4

 9CS2973
 CXA-0078-16-1-9CS2405
 CXA-0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000

 720451-000
 752687-000
 768146-000
 773159-000
 82841-877-5000
 83318E-009-500
 8348-060-500
 83653-002-5000

 83659-002-1000
 83709-002-1000
 8404-060-500
 8469
 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000

 8747-060-100
 8747-060-1000
 8769-060-1000
 8775-060-500
 8780-060-1000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060

 1000
 939870-000
 9423
 060U500
 8775-060-500
 8780-060-1000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060