

Product: <u>9778</u> ☑

Microphone Cable, 1 Conductor 20 AWG, TC



Product Description

20 AWG stranded (26x34) high-conductivity TC conductor, EPDM rubber insulation, conductive textile (100%) plus TC spiral shields (75% coverage), paper tape, CPE jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor					
AWG	Stranding	Material	Nominal Diameter	No. of Coax	
20	26x34	TC - Tinned Copper (High Conductivity)	0.037 in	1	
Conductor Count:			1		

Insulation

Material	Nominal Diameter
EPDM - Ethylene Propylene Diene Monomer	0.117 in

Outer Shield Material

Туре	Layer	Material	Coverage [%]
Spiral Serve / Screen	1	Textile (Conductive)	100%
Spiral Serve / Screen	2	Tinned Copper (TC)	75%
Таре	3		75%

Outer Jacket Material

Material	Nominal Diameter	Separator Material
Neoprene	0.235 in	Paper Tape

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
10.2 Ohm/1000ft	10.2 Ohm/1000ft	11.6 Ohm/1000ft	11.6 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield	1
45 pF/ft	ĺ

Impedance

Nominal Characteristic Impedance 40 Ohm

Current

Max. Recommended Current [A] 4 Amps per Conductor at 25°C

Voltage

Non-UL Voltage Rating

300 V RMS

Temperature Range

Non-UL Temp Rating:	0°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	34 lbs/1000ft
Max. Pull Tension:	13 lbs
Min Bend Radius/Minor Axis:	2.5 in

Standards

RG Type:	N/A	

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes				
Plenum/Non-Plenum					
Plenum (Y/N):	No				

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
9778 0101000	Chrome	Reel	1,000 ft	612825259640

History

Update and Revision:

Revision Number: 0.270 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory and regulatory because the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Coaxial Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

89880-003-1000 633948-877-1000 CY2389-000 8213-010-1000 8221-010-U1000 8233-010-1000 88281-010-500 1322R-010-1000 177799-000 1807A-B59-U1000 9167-010-1000 9251-010-1000 9275-010-U1000 935240-000 9659-010-1000 980704-001 CF2823-000 33312-010-500 CZ1589-000 5022W0809-0CS3263 10610-4-4 EF8108-000 1673B TIN100 672525-001 144517-000 8-1616396-1 8263-010-U1000 8263 010U500 8268-010-500 8262 010U1000 7915A 009U1000 5024A1311-0 TRC-75-1 1281S5 010250 1281S5 000250 1530A 010U1000 1505A 0081000 9248 010U1000 CO-142BNCX200-001 7809WB 010500 9244 0101000 1694A 0081000 9204 0101000 8241F J5C1000 1530A 0101000 1674A TIN50 7915A 0091000 7915A 010500 TWCH-78-2 TWC-78-1