


9830 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422

For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (7x32) TC conductors, polyethylene insulation, twisted pairs, overall Beldfoil® (100% coverage) + TC braid shield (65% coverage), 24 AWG stranded TC drain wire, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
3	24	7x32	TC - Tinned Copper

Total Number of Conductors: 6

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PE - Polyethylene	0.406

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	65

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.889

Overall Cable

Overall Nominal Diameter: 7.747 mm

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White
3	White/Green & Green/White

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +80°C

UL Temperature Rating: 80°C (UL AWM Style 2919)

Bulk Cable Weight: 71.434 Kg/Km

Min. Bend Radius/Minor Axis: 82.550 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

9830 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2919 (30 V 80°C)
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
100

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
50.8555

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)
90.2275

Nominal Velocity of Propagation:

VP (%)
66

Nominal Delay:

Delay (ns/m)
5.2496

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
78.744

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
14.4364

Max. Operating Voltage - UL:

Voltage	Description
30 V RMS	UL AWM Style 2919
300 V RMS	CM

Max. Recommended Current:

Current
2.1 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

METRIC MEASUREMENT VERSION

9830 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422

9830 0601000	1,000 FT	53.000 LB	CHROME	C	3 PR #24 PER SH PVC
9830 060500	500 FT	26.500 LB	CHROME	C	3 PR #24 PER SH PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 01-05-2015

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Belden](#) manufacturer:

Other Similar products are found below :

[0939 CTX 101](#) [1000A 0101000](#) [1000A-BLK-1000](#) [1030A 0061000](#) [1030A 0101000](#) [1031A 0101000](#) [1032A 0061000](#) [1032A 0101000](#)
[1032A-LT-BLU-1000](#) [1033A 0101000](#) [1033A-BLK-1000](#) [1034A 0101000](#) [1035A 0101000](#) [1035A-BLK-1000](#) [1036A 0101000](#) [10GB-B100](#)
[10GC-B100](#) [10GC-BC50](#) [10GD-B100](#) [10GX12 0061000](#) [10GX12-LT-BLU-1000](#) [10GX13 D151000](#) [10GX24-004-1000](#) [10GX32-006-1000](#)
[10GX32-LT-BLU-1000](#) [10GX44 0061000](#) [10GX53F-004-1000](#) [10GX53F-YEL-1000](#) [10GXS12 0061000](#) [10GXS13 0081000](#) [10GXS32](#)
[0091000](#) [10GXW13 0021000](#) [10GXW13 0031000](#) [10GXW13 0091000](#) [1121A 010500](#) [1152A-A8R-500](#) [11700A 0061000](#) [11700A 0101000](#)
[11700A-BLK-1000](#) [11700A-LT-BLU-1000](#) [1172A B59500](#) [1172A-BLK-MATTE-500](#) [1186A-010-1000](#) [1186A-BLK-1000](#) [1189A 0101000](#)
[1189A 010U1000](#) [1189A-290-1000](#) [1189A-BLK-1000](#) [1189A-LT-BGE-1000](#) [1190A 0101000](#)