

Product: <u>9912</u> ⊠	
Lead Wire, #12 Str TC, PVC	Ins, AWM 1015 AWM 123
😭 Request Sample	

Product Description

Low Temp Plastic Lead Wire, 12AWG (65x30) Tinned Copper, PVC Insulation, AWM 1015 AWM 1230 CSA TYPE TEW JQA-F 600V 105C

Technical Specifications

Product Overview

Suitable Applications: in		inter-connection circuits, interna	l wiring of computer and electronic equipments, internal wiring of appliances, machine tool wire
Construction	Details		
Conductor			
Size Stranding	Material		
12 65x30	TC - Tinned Copp	per	
nsulation Material	Nom. Th	ickness Nom. Insulation Dia	meter
PVC - Polyvinyl Chloride 0.035 in (0.89 mm) 0.158 in (4.01 mm)	
		0.158 in (4.01 mm)	

Electricals

Nom. Conductor DCR	Max. Current
1.65 Ohm/1000ft (5.41 Ohm/km)	Single conductor in free air @ 30°C: 51 A

Voltage

UL Voltage Rating 600 V RMS

Mechanical Characteristics

Temperature	
UL Temperature	Operating
105°C	-25°C To +105°C
Bulk Cable Weight:	:

Standards and Compliance

CA Prop 65
VW-1, FT1
Article 310, MTW or TW
UL AWM Styles 1015, 1230, CSA AWM I A/B
TEW
EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)

History

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 CR6328-000
 01776.38.01
 M22759/16-14-5-500FT
 7053-RED-1000
 7053-SLATE-1000
 F25935-000

 F60898-000
 8055
 81044/12-18-9CS3209
 82A0811-4-9-G110
 83004-ORG-1000
 83005-LT-BLU-1000
 83025-VIO-1000
 8523-RED-100

 8524-WHT-100
 8525-ORG-1000
 8530-BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 8898-BLK-100
 138498-000

 E76065-000
 EPD50886A-20-9
 BFWUL3239-24-PINK
 C2015A.12.04
 C2015A.12.05
 C2015A.12.10
 C2015A.12.19

 C2016A.12.05
 C2016A.12.07
 C2065A.12.02
 C77653-000
 220368-001
 8916-GRY-500
 8918-RED-100
 8919-DK-BLU-100
 8919-YEL-100

 8920-YEL-100
 9242833001
 933205-000
 2841/7-YELLOW-1000
 2842/7-ORANGE-100
 2842/7-RED-1000
 2843/19-BLUE-100
 2843/1

 YELLOW-100
 2843/7-GREEN-100
 100
 100
 100
 100
 100
 100
 100