



Product: <u>9964</u> ☑

Electronic, 4 C #20 Str TC, PVC-NYL Ins, OA TC Brd, PVC Jkt

Request Sample

Product Description

Electronic, 4 Conductor 20AWG (19x32) Tinned Copper, PVC-NYL Insulation, Overall Tinned Copper Braid(90%) Shield, PVC Outer Jacket

Technical Specifications

Product Overview

Suitable Applications: MIL-W-16878 (Type B) Spec; up to 600V analog signals; up to 600V voltage control

Construction Details

Conductor

| Element | Number of Element | Size | Stranding | Material |
|--------------|-------------------|------|-----------|--------------------|
| Conductor(s) | 4 | 20 | 19x32 | TC - Tinned Copper |

Insulation

| Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|--|----------------------|--------------------------|--------------------------|
| PVC/Nylon - Polyvinyl Chloride + Nylon | 0.0135 in (0.343 mm) | 0.064 in (1.6 mm) | White, Black, Red, Green |
| Nylon | 0.003 in (0.076 mm) | | |

Outer Shield

| Shield Type | Material | Coverage |
|-------------|--------------------|----------|
| Braid | Tinned Copper (TC) | 90% |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter |
|--------------------------|--------------------|---------------|
| PVC - Polyvinyl Chloride | 0.025 in (0.64 mm) | 0.226 in |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current |
|-----------------------|-------------------------------|---|--------------------------------|
| 9.1 Ohm/1000ft | 40 pF/ft (130 pF/m) | 100 pF/ft (330 pF/m) | 3.8 Amps per Conductor at 25°C |

Voltage

Voltage Rating 600 V

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|-----------------------|-----------------|
| 105°C | -20°C To +105°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 2.26 in (57.4 mm) | 2.26 in |

| Max. Pull Tension: | 60 lbs |
|--------------------|---------------|
| Bulk Cable Weight: | 35 lbs/1000ft |

Standards and Compliance

| Flammability / Reaction to Fire: | IEC 60332-1-2 |
|----------------------------------|--|
| CPR Compliance: | CPR Euroclass: Eca |
| Military Compliance: | MIL-W-16878E/17 (insulated conductor) |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Other Standard Compliance(s): | NEMA HP3 |

History

| Update and Revision: | Revision Number: 0.380 Revision Date: 12-19-2021 | |
|----------------------|--|--|

Variants

| Item # | Color | UPC |
|--------------|-------|--------------|
| 9964 009100 | White | 612825265276 |
| 9964 0091000 | White | 612825265283 |
| 9964 009500 | White | 612825265290 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

000581-000 00100004 00100014 00100024 00100034 0010004 0010005 0010006 0010007 0010008 0010009 0010012 00100214 00100224 00100234 00100244 0010025 0010026 0010027 0010028 0010029 0010030 0010031 0010032 0010034 00100414 00100424 00100434 0010044 0010045 0010046 0010047 0010049 0010050 0010052 0010053 0010054 0010056 00100634 00100644 00100654 00100664 0010068 0010069 0010071 0010072 0010074 0010076 0010086 0010087