

Lead Wire, #26 Sol TC, PVC Ins, AWM 1061	Produ	ct: <u>9976</u> ⊠			
M Demuset Comple	Lead	Vire, #26 So	I TC, PVC	C Ins, AWM 10	61
Request Sample		😭 Request	Sample		

# **Product Description**

Low Temp Plastic Lead Wire, 26AWG (Solid) Tinned Copper, PVC Insulation, AWM 1061 CSA AWM 300V 80C

### **Technical Specifications**

#### **Product Overview**

Suitable Applications:	inter-connection circuits, internal wiring of computer and electronic equipments, wire wrap applications
------------------------	--

### **Physical Characteristics (Overall)**

### Conductor

AWG	Stranding	Material	No. of Conductors
26	Solid	TC - Tinned Copper	1
Conduc	Conductor Count: 1		

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.036 in	0.01 in

#### **Electrical Characteristics**

#### Voltage

UL Voltage Rating 300 V RMS

# Temperature Range

Non-UL Temp Rating:	80°C
UL Temp Rating:	80°C

### **Mechanical Characteristics**

Bulk Cable Weight:	1.25 lbs/1000ft
Min. Bend Radius/Minor Axis:	0.15 in

#### **Standards**

UL Rating:	300V RMS, 80°C
UL AWM Style Compliance:	UL AWM Style 1061
CSA Rating:	300V RMS, 80°C
CSA AWM Compliance:	CSA AWM I A/B
CSA Type:	AWM I, A/B

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes

EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
CA Prop 65:	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

CSA Flammability:     FT1       UL voltage rating:     300 V RMS	UL Flammability:	VW-1
UL voltage rating: 300 V RMS	CSA Flammability:	FT1
	UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

		Plenum (Y/N):	No
--	--	---------------	----

#### **Part Number**

#### Variants

Item #	Color	Put-Up Type	Length	UPC
9976 010100	Black	Reel	100 ft	612825265672
9976 0101000	Black	Reel	1,000 ft	612825265689
9976 0131000	Blue, Dark	Reel	1,000 ft	612825265696
9976 0011000	Brown	Reel	1,000 ft	612825265566
9976 0081000	Gray	Reel	1,000 ft	612825265634
9976 0051000	Green, Dark	Reel	1,000 ft	612825265627
9976 0031000	Orange	Reel	1,000 ft	612825265597
9976 002100	Red	Reel	100 ft	612825265573
9976 0021000	Red	Reel	1,000 ft	612825265580
9976 009100	White	Reel	100 ft	612825265658
9976 0091000	White	Reel	1,000 ft	612825265665
9976 0041000	Yellow	Reel	1,000 ft	612825265603

Footnote:

P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

#### **History**

Update and Revision:

Revision Number: 0.361 Revision Date: 12-15-2021

#### © 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 CR6328-000
 01776.38.01
 M22759/16-14-5-500FT
 7053-RED-1000
 7053-SLATE-1000
 F25935-000

 F60898-000
 8055
 81044/12-18-9CS3209
 82A0811-4-9-G110
 83004-ORG-1000
 83005-LT-BLU-1000
 83025-VIO-1000
 8523-RED-100

 8524-WHT-100
 8525-ORG-1000
 8530-BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 8898-BLK-100
 138498-000

 E76065-000
 EPD50886A-20-9
 BFWUL3239-24-PINK
 C2015A.12.04
 C2015A.12.05
 C2015A.12.10
 C2015A.12.19

 C2016A.12.05
 C2016A.12.07
 C2065A.12.02
 C77653-000
 220368-001
 8916-GRY-500
 8918-RED-100
 8919-DK-BLU-100
 8919-YEL-100

 8920-YEL-100
 9242833001
 933205-000
 2841/7-YELLOW-1000
 2842/7-ORANGE-100
 2842/7-RED-1000
 2843/19-BLUE-100
 2843/1 

 YELLOW-100
 2843/7-GREEN-100
 100
 100
 100
 100
 100
 100
 100