



AX101314 Modular Connectors - CAT5E Modular Jack - KeyConnect



For more Information
please call

1-800-Belden1



General Description:

CAT5E Modular Jack, RJ45, KeyConnect style, Green (TIA 606)

Usage (Overall)

Suitable Applications: IBDN System 1200, TIA Category 5E, ISO Class D, 1000 BASE-T

Related Parts: Compatible with KeyConnect Faceplates, Adapters, Boxes and Patch Panels

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

| Height (mm) | Width (mm) | Depth (mm) |
|-------------|------------|------------|
| 22.352 | 16.256 | 32.766 |

Materials

Materials:

| Description | Type | Material |
|------------------|------------|---|
| Front Connection | Lead Frame | Copper Allow with 50u inch Gold over Nickel |
| Rear Connection | IDC | Copper Allow with Nickel Plating |
| Connector Body | | Plastic - UL940V-0 |

Color

Color: Green (TIA 606)

Wiring Scheme

Wiring Scheme: T568A/B

Weight

Weight: 0.006 kg

Included Parts

Included Parts: 1 T-Bar

Packaging

Packaging: Individually packaged in a plastic bag. Standard pack of 50 units.

Mechanical Characteristics (Connectivity)

Footprint/Type: KeyConnect

Plug / Jack Compatibility: RJ45, RJ11

Termination Interface:

| Termination | Connection | Durabilities |
|-------------|--------------------------|-----------------|
| Front | Mated Connection | 1,000 cycles |
| Rear | Gas Tight IDC Connection | 20 terminations |

Connector/Hardware Retention: 88.964 N

Plug/Connector Retention: 50.042 N

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Operating Temperature Range: -10°C To +60°C

AX101314 Modular Connectors - CAT5E Modular Jack - KeyConnect

Tool Compatibility: Belden 110 Connecting Tool, MediaFlex Termination Station

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|--|---|
| Other Standards: | FCC Part 68, Subpart F, IEC 60603-7 |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2006 |
| MII Order #39 (China RoHS): | EUP 50 |
| Telecommunications Standards: | Category 5e - TIA 568.B.2, Category 5 - ISO/IEC 11801:2002 Ed.2 |
| Third Party Performance Verification: | ETL - Verified Category 5e |
| Safety Listing: | ACA, Bi-national Standard Listed |

Suitability

Suitability - Indoor: Yes - Indoor

Transmission Characteristics (Connectivity)

Mated Connection Table 1:

| Frequency (MHz) | Max. Insertion Loss TIA* (dB) | Max. Insertion Loss Belden** (dB) | Min. NEXT TIA* (dB) | Min. NEXT Belden** (dB) | Min. FEXT TIA* (dB) | Min. FEXT Belden** (dB) |
|-----------------|-------------------------------|-----------------------------------|---------------------|-------------------------|---------------------|-------------------------|
| 1.000 | 0.100 | 0.100 | 65.000 | 77.000 | 65.000 | 77.000 |
| 4.000 | 0.100 | 0.100 | 65.000 | 73.800 | 63.100 | 74.800 |
| 8.000 | 0.100 | 0.100 | 64.900 | 67.700 | 57.000 | 68.700 |
| 10.000 | 0.100 | 0.100 | 63.000 | 65.800 | 55.100 | 66.800 |
| 16.000 | 0.100 | 0.100 | 58.900 | 61.700 | 51.000 | 62.700 |
| 20.000 | 0.100 | 0.100 | 57.000 | 59.800 | 49.100 | 60.800 |
| 25.000 | 0.100 | 0.100 | 55.000 | 57.800 | 47.100 | 58.800 |
| 31.250 | 0.110 | 0.100 | 53.100 | 55.900 | 45.200 | 56.900 |
| 62.500 | 0.160 | 0.120 | 47.100 | 49.900 | 39.200 | 50.900 |
| 100.000 | 0.200 | 0.160 | 43.000 | 45.800 | 35.100 | 46.800 |
| 160.000 | | 0.210 | | 41.700 | | 42.700 |

Mated Connection Table - Footnote:

* TIA/EIA-568-C.2 Category 5E Standard.
 ** Worst-case performance for a CAT5E mated connection using CAT5E modular plugs.

Mated Connection Table 2:

| Frequency (MHz) | Min. Return Loss TIA* (dB) | Min. Return Loss Belden** (dB) | Min. Balanced TCL Belden** (dB) |
|-----------------|----------------------------|--------------------------------|---------------------------------|
| 1.000 | 30.000 | 32.000 | 42.000 |
| 4.000 | 30.000 | 32.000 | 42.000 |
| 8.000 | 30.000 | 32.000 | 42.000 |
| 10.000 | 30.000 | 32.000 | 42.000 |
| 16.000 | 30.000 | 32.000 | 42.000 |
| 20.000 | 30.000 | 32.000 | 42.000 |
| 25.000 | 30.000 | 32.000 | 42.000 |
| 31.250 | 30.000 | 32.000 | 42.000 |
| 62.500 | 24.100 | 31.100 | 36.100 |
| 100.000 | 20.000 | 27.000 | 32.000 |
| 160.000 | | 22.900 | 27.900 |

Dielectric Strength: 1,000 V RMS @ 60 Hz for 1 minute

Current Rating: 1.500 A

Insulation Resistance: 500 M-Ohm Minimum

Max. Contact Resistance: 20 m-Ohm

Termination Resistance: 2.5 m-Ohm

AX101314 Modular Connectors - CAT5E Modular Jack - KeyConnect

Notes (Overall)

Notes: Please see Installation Guide PX103329

Notes (Cont'd.):

IDC Wire Gauge: 22~24 AWG

Product Family

Part Number List:

| Item Number | Color |
|-------------|------------------|
| AX101307 | Gray |
| AX101308 | Almond |
| AX101309 | Elec. White |
| AX101310 | Black |
| AX101311 | Orange (TIA 606) |
| AX101312 | Red (TIA 606) |
| AX101313 | Yellow (TIA 606) |
| AX101314 | Green (TIA 606) |
| AX101315 | Blue (TIA 606) |
| AX101316 | Purple (TIA 606) |
| AX101317 | Brown (TIA 606) |
| AX103079 | Ivory |
| AX104182 | Orange |
| AX104183 | Red |
| AX104184 | Yellow |
| AX104185 | Green |
| AX104186 | Blue |
| AX104187 | Purple |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------|-------|-------------|-------|-------|-------------------------------|
| AX101314 | 1 EA | 0.170 LB | | | CAT5E JACK KCONN GREEN TIA606 |

Revision Number: 1 Revision Date: 08-12-2014

© 2020 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [MP1010RX-1000](#) [MP44RX-1000](#) [PHJ-4P4C-1-V-4](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GAX-8-62](#) [GDCX-PA-66-50](#) [GDCX-PN-64](#) [GDCX-PN-66](#) [GDCX-PN-66-50](#) [GDLX-A-66](#) [GDLX-N-66](#) [GDLX-S-66](#) [GDLX-S-88K](#) [GDLX-SMT-S-88](#) [GDTX-S-88-50](#) [GDX-PA-1010](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#) [GMX-N-1010](#) [GMX-S-1010](#) [GMX-S-66](#) [GMX-SMT4-N-88](#) [GPX-2-64](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS2-88-3.05-50](#) [GSX-NS-88-3.05-50](#) [PT-108A-8C-UL](#) [PT-J951-8C](#) [PTS-J531-8CS-50UL](#) [1-1775629-2](#) [A-2014-0-4](#) [GWLX-S-88-GR](#) [GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1413235](#) [MP88X-1000](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [E5908-15A242-L](#)