



**Product:** MEDIAFLEX RCA INSERT ☑

RCA Insert for MediaFlex, 3-Port

# **Product Description**

MediaFlex RCA Insert, 3-Port, Available in several colors.

## **Technical Specifications**

## **Product Overview**

Environmental Space:	Indoor	
Suitable Applications:	Multimedia	

# **Physical Characteristics (Overall)**

Height:	1.39 m
Width:	2.05
Depth:	1.41
Packaging:	Individually packaged in a plastic bag.
Weight:	0.05 kg

## Connectors

## Materials

Description	Material	Type
Front Connection	Metal	RCA
Rear Connection	Plastic - UL94V-0	110
Insert	Plastic - UL94V-0	

# **Temperature Range**

Installation Temp Range:	-10 to 60°C
Storage Temp Range:	-40 to 70°C
Operating Temp Range:	-10 to 60°C

# **Mechanical Characteristics**

Footprint/Type:	Mediaflex
Tool Compatibility:	Termination Station (AX101852), Release Tool (AX101185)

# **Applicable Environmental and Other Programs**

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-01-07
MII Order #39 (China RoHS):	EUP 50

# Flammability, LS0H, Toxicity Testing

Safety Listing:	ACA, Bi-national Standard Listed

## **Part Number**

Related Parts:	Compatible with MediaFlex Faceplates

#### Variants

Item #	Color
AX101878	Almond
AX101880	Black
AX101877	Gray
AX102578	Ivory
AX101879	White
AX102616	White

#### **Product Notes**

Included Parts:	Pin assignement guide
Notes:	For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com

#### **History**

Update and Revision:	Revision Number: 0.150 Revision Date: 07-11-2019

#### © 2019 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RCA Phono Connectors category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

17PP052 NYS352AG 333-0000 330F3 336AX 342-0000 AP-165 598 AX101880 716SNS1P11PL-25 585 330-0000 335-0000 588

ACJD-BLK NF2D-2 NF2D-9 NF2D-B-0 NF2D-B-4 299 ACJD-RED ACJD-WHT PJRAS3X1S01X RCJ-2244 3507 413-0100 431-0500 331-0000 561 NF2D-B-2 NF2D-B-6 566 571 572 574 580 581 583 586 587 589 598 NYS354 NYS372P NYS373-2-U ACJD-GRN 936 PJRAN1X1U03AUX PJRAS1X3S02X 937