Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX102262 Faceplates and Panels - KeyConnect Blank Insert







For more Information please call

1-800-Belden1



General Description:

KeyConnect Blank Insert

Usage (Overall)

Related Parts: - Compatible KeyConnect-style Faceplate and Patch Panel

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (mm)	Width (mm)	Depth (mm)
21.590	16.510	20.066

Materials

Materials:

Description	Material	
Insert	Plastic - UL94V-0	

Color

Color: Elec. White

Weight

Weight: 0.001 kg

Packaging

Packaging: 50 units packaged in a plastic bag.

Mechanical Characteristics (Connectivity)

Footprint/Type:	KeyConnect	
Connector/Hardware Retention:	88.964 N	
Storage Temperature Range:	-40°C To +70°C	
Installation Temperature Range:	-10°C To +60°C	
Operating Temperature Range:	-10°C To +60°C	

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

Suitability - Indoor:	Yes
Suitability	
Safety Listing:	Bi-national Standard Listed
MII Order #39 (China RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
EU Directive 2002/95/EC (RoHS):	Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Page 1 of 2 03-07-2019

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX102262 Faceplates and Panels - KeyConnect Blank Insert

Notes: For proper installation refer to Installation Guide PX103826. Visit our web site at http://www.belden.com/pdfs/Techpprs/InstallationGuide.pdf

Product Family

Part Numbers:

Item Number	Color	
AX102261	Almond	
AX102262	Elec. White	
AX102263	Black	
AX104229	Ivory	
AX104456	Dark Gray	
AX107026	Light Gray	

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102262	1 EA	0.002 KG			KCONN BLANK MODULE, ELEC WHITE

Revision Number: 0 Revision Date: 10-18-2016

© 2019 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2 03-07-2019

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting & Raceways category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

```
800A-LB 801I-LSP 802A-ECSP 802I-ICSP 923223-000 PRAF6WH-X A0405538 1301150342 1301160034 1301170070 1301180011 1301230083 1301230153 1301240273 1301250006 1302261238 1302261321 1302262552 1302263103 1302263178 1302263259 1302263816 1302263860 1302264375 1302264390 1301150343 1301160030 1301170050 1301170051 1301170061 1301180013 1301230086 1301230130 1301240054 1302260055 1302260376 1302261343 1302261344 1302262674 1302263095 1302263166 1302263209 1302263513 1302263851 1302263870 1302264137 1302264218 DD1/J AX102007 AX102411
```