## **Detailed Specifications & Technical Data**



#### METRIC MEASUREMENT VERSION

### AX102413 Faceplates and Panels - MediaFlex Keyconnect Style insert 2-port, Angled







For more Information please call

1-800-Belden1



#### **General Description:**

Kit of 10 MediaFlex KeyConnect Module Insert, 2-port, angled, white

| sage (Overall)   |  |  |  |
|--|--|--|--|
| Suitable Applications:   | - Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800,3600, 2400 and 1200.     - Compatible with 10GX, CAT6+ and CAT5E Keyconnect-style Modular Jacks and Keyconnect Multimedia Modules |  |  |
| Related Parts:   |  |  |  |
| hysical Characteristics (Connectivity)   |  |  |  |
| Capacity   |  |  |  |
| Max. Capacity:   | 2 Inserts  |  |  |
| Access   |  |  |  |
| Front Connection:  | Angled   |  |  |
| Dimensions<br>Dimensions:  |  |  |  |
| Height (mm)         Width (mm)         Depth (mm)           35.306         52.070         13.970 |  |  |  |
| Materials<br>Materials:  |  |  |  |
| Description         Material           Inserts         Plastic - UL94V-0                         |  |  |  |
| Color  |  |  |  |
| Color:   | Elec. White  |  |  |
| Weight   |  |  |  |
| Weight:  | 0.005 kg   |  |  |
| Packaging  |  |  |  |
| Packaging:   | 10 inserts packaged in a suitable plastic bag  |  |  |
| lechanical Characteristics (Connectivity)  |  |  |  |
| Connector/Hardware Retention:  | 88.964 N   |  |  |
| Storage Temperature Range:   | -40°C To +70°C   |  |  |
| Installation Temperature Range:  | -10°C To +60°C   |  |  |
| Operating Temperature Range:   | -10°C To +60°C   |  |  |
| Tool Compatibility:  | Termination Station (AX101852), Release Tool (AX101185)  |  |  |
| pplicable Specifications and Agency Compliand  | ce (Overall)   |  |  |
| Applicable Standards & Environmental Programs  |  |  |  |
| EU Directive 2002/95/EC (RoHS):  | Yes  |  |  |
| EU RoHS Compliance Date (mm/dd/yyyy):  | 07/01/2006   |  |  |
| MII Order #39 (China RoHS):  | Yes  |  |  |
| Safety Listing:  | ACA, Bi-national Standard Listed   |  |  |
| Suitability  |  |  |  |
| Suitability - Indoor:  | Yes  |  |  |
| lotes (Overall)  |  |  |  |
|  | 2063 available on our web site at http://www.belden.com/pdfs/Techpprs/InstallationGuide.pdf  |  |  |

#### Part Numbers: Item Number Color



#### METRIC MEASUREMENT VERSION

#### AX102413 Faceplates and Panels - MediaFlex Keyconnect Style insert 2-port, Angled

| AX102412 | Almond      |
|----------|-------------|
| AX102413 | Elec. White |
| AX104483 | Grey        |
| AX102738 | Black       |

#### **Put Ups and Colors:**

| Item #   | Putup | Ship Weight | Color | Notes | Item Desc                      |
|----------|-------|-------------|-------|-------|--------------------------------|
| AX102413 | 1 EA  | 0.173 LB    |       |       | KIT MFLEX KCONN INSERTS(10/PK) |

Revision Number: 0 Revision Date: 08-08-2012

## © 2017 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in the ore that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting & Raceways category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 800A-LB
 801I-LSP
 802A-ECSP
 802I-ICSP
 923223-000
 PRAF6WH-X
 A0405538
 1301150342
 1301160034
 1301170070
 1301180011

 1301230083
 1301230153
 1301240273
 1301250006
 1302261238
 1302261321
 1302262552
 1302263103
 1302263178
 1302263259

 1302263816
 1302263860
 1302264375
 1302264390
 1301150343
 1301160030
 1301170051
 1301170061
 1301180013

 1301230086
 1301230130
 1301240054
 1302260055
 1302260376
 1302261343
 1302262674
 1302263095
 1302263166

 1302263209
 1302263513
 1302263870
 1302264137
 1302264218
 DD1/J
 AX102007
 AX102261