Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX102907 Faceplates and Panels - KeyConnect Video F Coax, Surface



Part Numbers:

Item Number Color

AX102906 Almond





For more Information please call

1-800-Belden1



Canaval Pagavintian	
General Description:	
KeyConnect Video F, Coax, Surface	
Usage (Overall)	
Suitable Applications:	- Coax
Related Parts:	- Compatible KeyConnect-style Faceplate and Patch Panel
Physical Characteristics (Connectivity)	
Capacity	
Access Front Connection:	Flush
	riusii
Dimensions Dimensions: Height (mm) Width (mm) Depth (mm) 21.590 17.526 29.972	
Materials Materials: Description Material Insert Plastic - UL94V-0	
Color	
Color:	Elec. White
Weight	
Weight:	0.015 kg
Packaging	
Packaging:	10 units packaged in a plastic bag.
	10 units packaged in a plastic bag.
Packaging:	10 units packaged in a plastic bag. KeyConnect
Packaging: Mechanical Characteristics (Connectivity)	
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type:	KeyConnect
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention:	KeyConnect 88.964 N
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range:	KeyConnect 88.964 N -40°C To +70°C
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range:	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range:	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS):	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Everall) Yes
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy):	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Verall) Yes 07/01/2006
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): MII Order #39 (China RoHS):	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Verall) Yes 07/01/2006 Yes
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): MII Order #39 (China RoHS): Safety Listing:	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Verall) Yes 07/01/2006 Yes
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): MII Order #39 (China RoHS): Safety Listing:	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Verall) Yes 07/01/2006 Yes Bi-national Standard Listed
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): MII Order #39 (China RoHS): Safety Listing: Suitability Suitability - Indoor: Transmission Characteristics (Connectivity)	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Verall) Yes 07/01/2006 Yes Bi-national Standard Listed
Packaging: Mechanical Characteristics (Connectivity) Footprint/Type: Connector/Hardware Retention: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Agency Compliance (O Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): MII Order #39 (China RoHS): Safety Listing: Suitability Suitability Suitability - Indoor:	KeyConnect 88.964 N -40°C To +70°C -10°C To +60°C -10°C To +60°C Verall) Yes 07/01/2006 Yes Bi-national Standard Listed Yes

Page 1 of 2 03-13-2017

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX102907 Faceplates and Panels - KeyConnect Video F Coax, Surface

AX102907	Elec. White
AX102908	Black
AX104567	Ivory
AX105384	Dark Gray

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102907	1 EA	0.015 KG			KCONN F-COAX MODULE E-WH

Revision Number: 0 Revision Date: 08-14-2012

© 2017 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connector Accessories category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

89674-0712 F702RX24 FERRULE-174 R141802000 R141805000 R141842000 R161862000 R161862000 R280752000 R280907000 R694261906 RFI21-13 RFI75-13-D2 RFI75-4-D2 AX102906 AX102907 18097-0013 HP-375 HP-500 2098-0294-00 2098-3251-94 KA-81-05 89674-0805 F1 FERRULE-223 202102-11 213337-1 220222-2 24092671A 24092678A R280468000 R280510000 R282862060 RFI155-1 RFI25-12-D3 RFI25-5-D3 RFI75-12-D2 RFI75-2-D2 RFI75-4-D3 RFI77-6 360HS001M2508M6 4-1532137-4 5-21085-0 105274-1000 111062-0490 112122-SOD-LUG 112-NUT-KNURL IPP-2014 R280490020