Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX103912 Faceplates and Panels - FiberExpress Ultra Splice Tray 8 inches

N N

For more Information please call

1-800-Belden1



General Description: FiberExpress Ultra 8 inches Splice Tray Usage (Overall) Suitable Applications: FiberExpress Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers Related Parts: FiberExpress Ultra 4U Rack Mount And Wall Mount Patch Panels Physical Characteristics (Connectivity) Capacity Max. Capacity: Optimal 24 Splices **Dimensions** Dimensions: Height (mm) Width (mm) Length (mm) 13.970 114.300 Materials Description Material Color Splice Tray | Metal Weight Weight: 0.318 kg **Packaging** Packaging: Individually packaged in a plastic bag, Shipped in cardboard box (25/box) **Mechanical Characteristics (Connectivity)** Storage Temperature Range: -40°C To +80°C **Operating Temperature Range:** -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs** EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Suitability Suitability - Indoor: Yes **Transmission Characteristics (Connectivity)** Notes: For additional information about this product refer to product buletin NP286, or visit our web site at http://www.belden.com. **Product Family** Part Numbers: Description FiberExpress Ultra Splice Tray 8 inches | AX103912 FiberExpress Ultra Splice Tray 10 inches AX103913

Put Ups and Colors:

FiberExpress Ultra Splice Tray 12 inches AX103914

14 44	Destance	Oblin Market	0-1	NI-4	Harry Danes
Item #	Putup	Ship Weight	Color	Notes	item Desc

Page 1 of 2 06-15-2018

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX103912 Faceplates and Panels - FiberExpress Ultra Splice Tray 8 inches

Revision Date: 09-11-2009 Revision Number: 0

© 2018 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/5FC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fibre Optic Connectors category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

0004700001 6100-R 6313 F709034706 F709722200 F709730000 F718183204 F727403500 F727752800 8119 9440F20-27S-190 944-120-6001 9441F10SL-3S 9444W28-21S 9444W36-10S 9446F10SL-4S 9446W20-16S 953-101-5310-P 954-101-57202B A0270169 12-9122 12-5702 AX101713 AX102420 AX103923 AX104024 AX104193 AX104230 AX104498 AX104562 AX105203-B25 AX105205-S1 EHSC2M 181-011-126 181-011-S 181-057-126 HRFC-R2(40) NKSOPBUY 20500002116 2064996-1 20800001065 2170 9132 2612 2620 9291 9440F16-10S 9440F20-18S 9442W14S-10P 9446F16-10S-190