


H155A01

Wireless coax
50 Ohm transmission cable
Coax H155A01 AL PE



Applications

- 50 Ohm low loss coaxial transmission cable designed according European Standard EN 50117-1
- Operating frequencies between 5 and 6000 MHz

General Standards

- European standard EN 50117-1 and EN 50117-2-5
- European standard EN 50290-2-20

Construction & Dimensions

1. Inner conductor	
Material	stranded bare copper 19x0.28 mm
Diameter	1.41 mm ± 0.03 mm
2. Dielectric	
Material	Gas injected PE
Diameter	3.9 mm ± 0.15 mm
Centricity	≥ 85%
3. Foil	
Material	AL-PET-AL
Overlap	≥ 2 mm
4. Braid	
Material	tinned copper
Diameter	4.5 mm ± 0.25 mm
Coverage braid	80% ± 5%
5. Sheath	
Material	PE
Diameter	5.4 mm ± 0.2 mm

Mechanical characteristics

Parameter	Specification	Unit
Tensile strength of sheath	≥ 12.5	N/mm ²
Elongation at break of sheath	≥ 150	%
Adhesion dielectric @ 25 mm	5-50	N
Crush resistance of cable (load of 700N)	< 1	%
Maximum tensile strength of cable	100	N
Minimum static bend radius	60	mm

Electrical characteristics

Test methods in accordance with European standard EN 50117-1

Parameter	Specification	Unit
Mean characteristic impedance	50 ± 3	Ω
Regularity of Impedance	> 40	dB
DC loop resistance	≤ 32.4	Ω/km
DC resistance inner conductor	≤ 15.4	Ω/km
DC resistance outer conductor	≤ 17	Ω/km
Capacitance	84 ± 3	pF/m
Velocity ratio	80% ± 2%	
Insulation resistance	> 10 ⁴	MΩ.km
Voltage test of dielectric	2	kVdc
Screening Attenuation		
	30-1000 MHz	≥ 85
Return loss at		
	5-30 MHz	≥ 20*
	30-470 MHz	≥ 20*
	470-1000 MHz	≥ 18*
	1000-2000 MHz	≥ 16*
	2000-3000 MHz	≥ 15*
	3000-6000 MHz	≥ 15**
	* Maximum 3 peaks 4 dB lower then specified.	
	** Values above 3000 MHz for information only.	

Attenuation at:	Nominal	Unit
5 MHz:	2.5	dB/100m
50 MHz:	6.9	dB/100m
100 MHz:	9.1	dB/100m
230 MHz:	13.4	dB/100m
400 MHz:	18.0	dB/100m
800 MHz:	26.1	dB/100m
862 MHz:	27.3	dB/100m
1000 MHz:	29.6	dB/100m
1350 MHz:	34.9	dB/100m
Maximum attenuation is 10% higher		

Attenuation at:	Nominal	Unit
1750 MHz:	40.3	dB/100m
2150 MHz:	46.0	dB/100m
2400 MHz:	49.1	dB/100m
3000 MHz:	56.3	dB/100m
3600 MHz:	62.9	dB/100m
4200 MHz:	69.1	dB/100m
4800 MHz:	75.1	dB/100m
5400 MHz:	80.8	dB/100m
6000 MHz:	86.5	dB/100m

Environmental and overall characteristics

Parameter	Specification	Unit
Storage/operating temperature	-30 to +70	°C
Minimum installation temperature	-5	°C
Amount of halogen acid gas acc. to IEC 60754-1/2 & EN50267-1/2; pH	> 4.3	
Amount of halogen acid gas acc. to IEC 60754-1/2 & EN50267-1/2;	< 10	µS/mm



Belden declares this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [7810SB-010-1000](#) [9116-010-U500](#) [9272-006-500](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [275604-000](#) [935240-000](#)
[9659-010-1000](#) [980704-001](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#)
[735A1-008-1000](#) [8212-010-U500](#) [8263 010U500](#) [TCC-75-2](#) [9248 010U1000](#) [1694A 0081000](#) [8241F J5C1000](#) [7805R 008100](#) [9271 0061000](#)
[5339Q5 009U500](#) [89207 010100](#) [1369R 004500](#) [7915R 0101000](#) [833101-000](#) [1152A-A8R-500](#) [9907-E4X-U1000](#) [3092A-X7E-500](#) [100066-](#)
[0049](#) [5021K1011-0](#) [ECJ5048-L](#) [4505R 0071000](#) [T-RAD-400-FR](#) [2410329-4](#) [L01030B0021](#) [60.7500-23](#) [51305](#) [BU-4150031024](#) [0026010](#)
[L01001C0003](#) [BU-4150030024](#) [BU-4150032048](#) [SMBM-SMBM17410](#) [50942](#)