



For more Information
please call

1-800-Belden1



General Description:

3 Meter HDMI Assembly. HDMI Composite Cable - 4 pairs (26 AWG stranded (7x34) bare copper conductors, foam polyolefin insulation, individual Beldfoil® shield (100% coverage) with drain wire; 7 conductors (26 AWG stranded (7x34) tinned copper conductors, polyolefin insulation); overall Beldfoil® shield (100% coverage) plus tinned copper braid shield (75% coverage) with drain wire, FR-PVC jacket.

Usage (Overall)

Suitable Applications: HDMI Interfaces

Twisted Pair

Physical Characteristics

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material | Dia. (in.) |
|---------|-----|-----------|--------------------|------------|
| 4 | 26 | 7x34 | BC - Bare Copper | 0.019 |

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| Foamed Polyolefin |

Individual Shield

Individual Shield Material: Aluminum Foil-Polyester Tape

Individual Shield Drain Wire:

| AWG | Stranding | Conductor Material |
|-----|-----------|--------------------|
| 26 | 7x34 | TC - Tinned Copper |

Electrical Characteristics

Nom. Characteristic Impedance:

| Description | Impedance (Ohm) | Tolerance |
|--------------|-----------------|-----------|
| Shield Pairs | 100 | ± 10 |

Nominal Delay:

| Description |
|-----------------------------|
| Between Pairs |
| Between Conductors of Pairs |

Nominal Delay Skew:

| Description | Delay Skew (ps/ft) |
|----------------------------|--------------------|
| Between Pairs | 6.87 |
| Between Conductors of Pair | 3.14 |

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 19.300 Ohm/1000 ft

Nominal Outer Shield DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 4.900 |

Nominal FEXT:

| Description | FEXT |
|-----------------|----------|
| 1 MHz - 5.1 GHz | -26.7 dB |

Nom. Attenuation:

| Description | Freq. (MHz) | Attenuation (MHz) |
|---|-------------|-------------------|
| @ 25°C of Clock and Data pairs | 825.000 | -0.5 dB/ft |
| @ 25°C of Clock and Data pairs (Freq. in GHz) | 2.475 | -1.9 dB/ft |
| @ 25°C of Clock and Data pairs (Freq. in GHz) | 4.125 | -2.3 dB/ft |
| @ 25°C of Clock and Data pairs (Freq. in GHz) | 5.100 | -3.0 dB/ft |

Multi Conductor

Physical Characteristics

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material | Dia. (in.) |
|--------------|-----|-----------|--------------------|------------|
| 7 | 26 | 7x34 | TC - Tinned Copper | 0.019 |

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Individual Shield

Electrical Characteristics

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 37.300 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

Max. Recommended Current:

| Description | Current |
|------------------------------|----------|
| per Conductor @25°C (24 AWG) | 1.6 Amps |

Physical Characteristics (Overall)

Outer Shield

Outer Shield Material:

| Layer # | Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|---------|-------------------------|-------|------------------------------|--------------|
| 1 | Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100.000 |
| 2 | | Braid | TC - Tinned Copper | 75.000 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 26 | 7x34 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--|
| F-R PVC - Flame Retardant Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter: 0.323 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Max. Recommended Pulling Tension: 99 lbs.

Min. Bend Radius/Minor Axis: 3.250 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2, CM

| | |
|--|------------|
| CEC/C(UL) Specification: | CM |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/21/2008 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flame Test

| | |
|-----------------------|----------------------|
| UL Flame Test: | UL1581 Vertical Tray |
|-----------------------|----------------------|

Plenum/Non-Plenum

| | |
|----------------------|----|
| Plenum (Y/N): | No |
|----------------------|----|

Electrical Characteristics (Overall)

| | |
|---|---|
| Other Electrical Characteristic 1: | 720P/1080i Verified (Category 1), 1080P Verified (Category 2) |
|---|---|

Related Documents:

[HDMI.pdf](#) - HDMI document

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0 Revision Date: 05-06-2013

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [HDMI Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[426301400-3](#) [68767-0003](#) [CA-MINIDP-HDMIF-10FT](#) [HP-19AFMM-SL7A01](#) [HP-19AFMM-SL7A05](#) [S-HDI-DVI-2](#) [S-HDI-DVI-5](#) [10HM-15128-01](#) [HD0003](#) [31888](#) [31889](#) [31893](#) [31897](#) [31907](#) [31908](#) [31911](#) [31913](#) [31914](#) [31915](#) [31919](#) [31920](#) [31921](#) [31923](#) [31925](#) [31926](#) [31929](#)
[31930](#) [31932](#) [31935](#) [31936](#) [31937](#) [31938](#) [CV0036B](#) [CV0038](#) [CV0055](#) [CV0057](#) [CV0058](#) [CV0058B](#) [CV0059B](#) [50580](#) [50581](#) [50582](#)
[50989](#) [51579](#) [51586](#) [51758](#) [51957](#) [52859](#) [31890](#) [31891](#)