




**Product:** [IEA003](#) 

DataTuff® 6A, 4 Bonded-Pr #23 Sol BC, FEP Ins, FEP Jkt, CMP, Extreme Temp.

## Product Description

Industrial Ethernet Cat 6A, 4 Bonded-Pair 23AWG (Solid) Bare Copper, FEP Insulation, Patented X-Spline & EquiBlock™ Technologies, FEP Outer Jacket, CMP, Oil/Sun Res., Extreme Temperature

## Technical Specifications

### Physical Characteristics (Overall)

Bonded-Pair:	Yes
--------------	-----

### Outer Jacket Material

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	0.263 in

### Temperature Range

Installation Temp Range:	-55°C To +150°C
UL Temp Rating:	150°C
Storage Temp Range:	-70°C To +150°C
Operating Temp Range:	-70°C To +150°C

### Mechanical Characteristics

Bulk Cable Weight:	39 lbs/1000ft
--------------------	---------------

### Standards

Telecommunications Standards:	ANSI/TIA-568-D.2 Category 6A
IEEE Specification:	802.3

### Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2011-12-09
---------------------------------------	------------

### Suitability

Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

### Part Number

Non-Plenum Number:	IEA001
Patent:	<a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a>

### Product Notes

Notes:	Operating temperature subject to length de-rating. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	---

### History

Update and Revision:	Revision Number: 0.8 Revision Date: 03-06-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Belden](#) manufacturer:*

Other Similar products are found below :

[01342.35T.01](#) [CS2885-000](#) [CTC-0062-20-9/5-9](#) [644833-000](#) [6500FE-877-1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CY0660-000](#) [730859-000](#) [MCC-USB-4-250](#) [768146-000](#) [773159-000](#) [820457-000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#) [83023-YEL-500](#) [83027-RED-100](#) [83029-GRN-100](#) [8302-CHR-500](#) [83046-RED-100](#) [8305-CHR-100](#) [83306E-WHT-100](#) [83333-WHT-100](#) [8334-060-1000](#) [83349E-WHT-100](#) [83652-RED-100](#) [8404-060-500](#) [8441-BLK-1000](#) [8450-BLK-1000](#) [8451-GRY-U500](#) [8459-CHR-500](#) [8465-CHR-1000](#) [8467-CHR-1000](#) [8469 060100](#) [8469-CHR-1000](#) [8471-CHR-1000](#) [8472-BLK-250](#) [8501-ORG-100](#) [8501-RED-100](#) [8503-WHT/BLU-100](#) [8520-BRN-100](#) [8520-GRY-100](#) [8523-GRY-100](#) [8523-GRY-1000](#) [8523-LT-BLU-25](#) [8523-ORG-1000](#) [8524-DK-BLU-100](#)