## **Detailed Specifications & Technical Data**



METRIC MEASUREMENT VERSION

## F81 Drop Connectors - Precision F81 Connector 3 GHz "F" Female Splice



For more Information please call

1-800-Belden1



## **General Description:** Precision F81 Connector 3 GHz "F" Female Splice, Splice Usage (Overall) Suitable Applications: Broadband, CATV Physical Characteristics (Connectivity) Product Family: Part Number Cable O.D. (mm) Description Inner Pack Outer Pack TBCF81 Precision F81 Connector 3 GHz F Female Splice 100 1.067 2000 Connector Type: Precision Splice Body: Zinc Body Finish: Nickel Mechanical Characteristics (Connectivity) Cable Retention Force: 200 grams Temperature Rating: -40°C To +70°C Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs** EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 11/27/2008 **Electrical Characteristics (Overall)** Frequency Range: 5 MHz TO 3 GHz Nominal Impedance: 75 Ohms Return Loss (typical): >= -24 dB up to 3 GHz, >=-30 dB up to 1 GHz Insertion Loss: <=-0.20 dB up to 1 GHz, <= -0.25 dB up to 3 GHz Shielding Effectiveness (Min.): 100 dB Band Flatness (min.): 0.1 dB @ 3 GHz Put Ups and Colors:

Item # Putup Ship Weight Color Notes Item Desc

Revision Number: 0 Revision Date: 08-26-2011

© 2016 Belden, Inc All Rights Reserved

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided of the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connector Accessories category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89674-0712
 FERRULE-174
 R125802000
 R141802000
 R141842000
 R141862000W
 R280752000
 R280907000
 RFI75-3
 AX102907
 HP 

 500
 2098-3251-94
 KA-81-05
 89674-0805
 F1
 FERRULE-223
 213337-1
 R280468000
 R280510000
 RFI25-12-D3
 RFI25-5
 RFI75-2-D2

 RFI75-4-D3
 RFI97-14
 3550
 04
 K00
 360HS001M2508M6
 4-1532137-4
 HRM-514S(40)
 XC0600B-03P
 5-21085-0
 111062-0490
 112122 

 SOD-LUG
 IPP-2014
 RFI95-14-D2
 LPTW2TP-124
 MX-913/U(45)
 R201450001
 1736-1511-075
 32Z112-000F
 000-78400
 78\_Z-7-3-4

 56Z112-000N
 RFI75-2-D3
 32Z111-000L5
 RG6WRO
 47140003A
 RFI75-2-D4
 RFI25-3-D3
 53919000B
 R280469010