
	TECHNICAL DATA SHEET	code	YE00820
		version	1
	EIB cable 4x0.8B PVC FS PVC	date	2008-06-30
		page	1/2

APPLICATION

EIB cable for building management.

CONSTRUCTION



1. Conductor

Diameter of conductor
Material

0.8 mm (0.5mm²)
solid bare copper

2. Insulation

Material
Diameter over insulation
Wallthickness

PVC
1.40 ± 0.05 mm
0.3 mm

3. Overall Cabling

Colour code

four wire into a quad
white-red-yellow-black
Cable core is wrapped with a PET
or PP foil (overlap > 15%)
< 80 mm

Laylength

4. Outer shield


Shield
Shield Material
Shield Thickness Alu
Shield coverage
Drainwire

Beldfoil®)
Aluminium / Polyester tape
9 µm
100%
0.4 mm Solid tinned Cu

4. Sheath

Material
Colour
Nominal thickness
Nominal diameter
Cable has a round appearance, sheath easy to remove.

PVC (like RAL 6017)
Green
1.2 mm
6.1 mm +/- 0.3 mm

	TECHNICAL DATA SHEET	code	YE00820
		version	1
	EIB cable 4x0.8B PVC FS PVC	date	2008-06-30
		page	2/2

REQUIREMENTS AND TEST METHODS

Electrical:

Maximum resistance conductor	34 Ω /km
Maximum capacitance conductor-conductor	100 nF/km
Testvoltage conductor-conductor	1000 VDC, 1 min.
Testvoltage conductor-screen	1000 VDC, 1 min.

Mechanical and physical:

Flame resistance	IEC 60332-1
Temperature range processing and operating	-20 to +70 °C
Temperature range storage	-30 to +70 °C
Minimum bending/setting radius	5*D/10

Cableprint: (in black ink) once every meter.

(WW/YY week and year nr of production, xxxx M = metermarking)

“BELDEN (TM) YE00820 EIB 2X2X0.8 MM WW/YY xxxx M REG NR. 109/7253/05”



Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[0152660053](#) [603020002](#) [73-7797-25](#) [73-8890-10](#) [73-8890-14](#) [73-8891-14](#) [73-8891-25](#) [73-8892-50](#) [73-8894-10](#) [73-8894-3](#) [73-8895-14](#) [73-8896-7](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [9QA0-111-12-3.00](#) [1200650742](#) [1200700174](#) [1200860368](#) [1200650013](#) [1201080008](#) [1-21919-1](#) [1300500373](#) [1300101844](#) [1300101845](#) [130050-0004](#) [1300500014](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [MT14-187L](#) [17-103530](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC30BLY](#) [NK5EPC30VLY](#) [NK5EPC30YLY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [NK6PC30BUY](#) [NK6PC30GRY](#) [NK6PC30RDY](#) [NK6PC30Y](#) [NK6PC30YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#)