



SMA to SMPM Adapters

Cinch Connectivity Solutions' Johnson SMA/SMPM adapters are available in combinations of plug to plug, plug to jack, and jack to plug, and jack to jack and are designed for use in most high frequency applications.

All Johnson high frequency connectors and adapters are designed to provide the highest quality data signal transmission.

Features

- VSWR: 1.20 Max DC to 20 GHz
 - 1.25 Max 20-26.5 GHz
- Insertion Loss: $0.12\sqrt{(F)}$ dB max (F in GHz)

Applications

- Test and Measurement lab equipment
- Semiconductor ATE test board
- Instrumentation test fixture hardware
- Communication and computer networks

Adapters (Between Series)

Part Number	Interface	Frequency	VSWR
134-1001-001	SMA Plug to SMPM Plug	DC to 26.5 GHz	1.20 Max DC to 20 GHz 1.25 Max 20-26.5 GHz
134-1001-002	SMA Plug to SMPM Jack		
134-1001-003	SMA Jack to SMPM Jack		
134-1001-004	SMA Jack to SMPM Plug		

Europe, Middle East & Africa

cinchconnectivity@eu.cinch.com

+44 (0) 1245 342060



Asia Pacific +86 21 5442 7668 ccs.asia.sales@as.cinch.com

North America +1 507 833 8822 ccsorders@us.cinch.com

© 2021 Cinch Connectivity Solutions

belfuse.com/cinch ds-ccs-johnson-sma-smpm-adapters-01142021

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - Between Series category:

Click to view products by Bel Fuse manufacturer:

Other Similar products are found below :

5945-9503-000 MCX/F-SMA/M R192417010 ADBJ20-E1-BJ379 ADM2 ADPL75-A1-PL75 242191 9317505 29-3835P AD130 ADBJ20-E1-PL74 ADBJ20-E2-BJ79 ADBJ77-A1-PL375 ADBJ77-E1-UPL20 ADRMF370 242228 R125680000W R192430000 UAD95 1057367-1 8311505 R114704000 R451034500 R451030500 R451543000 HDVDPN ADBJ20-K1-PL20 R451570000 R451034000 J9 J3WE-5 R451032500 242201RP 17K132-K00S5 AD-RSMAF-RTNC 53K156-K00N5 02K119-K00E3 29S132-K01N5 53S156-K00N5 02S119-S00E3 28K132-K00N5 02S109-K00S3 27-8200TP 242235 ADBJ20-E1-BJ89 AD-MQF-QCM-PM-2.5 AD-QCF-QCF-SP-2.5 AD-HQM-QCM-PM-2.5 1116-6094 1116-6095