

# Attenuators

## SMA Subminiature "MINIPAD"®

### DC - 26.5 GHz High Performance

- DC-2, DC-8, DC-12.4, and DC-18 GHz units available
- Rugged Stainless Steel Construction
- Any Male/Female combination available
- Low cost alternatives available

Midwest Microwave's SMA subminiature series of fixed coaxial attenuators (MINIPAD®) provide temperature stable, ruggedly built, precision performance in a compact light weight package size. Attenuation values up through 30 dB in 1 dB increments are available with any of the units described and with any combination of female or male SMA connectors.

#### SPECIFICATIONS - HIGH PERFORMANCE

**Frequency:** DC - 18.0, DC - 12.4, DC - 8.0 GHz  
DC - 4.0, and DC - 2.0 GHz

**Attenuation Accuracy:** 1-6 dB ± 0.3dB  
7-20 dB ± 0.5 dB  
21-30 dB ± 1.0 dB

**VSWR:** 1.07+.015 (f GHz) max.

**Power:** 2 Watts Average @ +25°C derated linearly to .5 watts @ +125°C

**Peak Power:** 200 Watts

**Operating Temperature Range:** -65 to +125C


**Finish:** Passivated Stainless Steel



#### TYPE II LOW VSWR - HIGH PERFORMANCE IMPROVED SPECIFICATIONS

Frequency GHz	VSWR
DC - 4.0 GHz	1.12 max
4.0 - 8.0 GHz	1.15 max
8.0 - 18 GHz	1.20 max

DC - 26.5 GHz		298 Series	Model Numbers
Male/Female	Female/Female	Male/Male	
ATT-0298-XX-SMA-02	ATT-298F-XX-SMA-02	ATT-298M-XX-SMA-02	
XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available)			
<i>HIGH PERFORMANCE</i>			



Attenuation Value	Length A
1-12 dB	0.86
13-30 dB	1.02

DC - 18 GHz		290 Series	Model Numbers
Male/Female	Female/Female	Male/Male	
ATT-0290-XX-SMA-02	ATT-290F-XX-SMA-02	ATT-290M-XX-SMA-02	
XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available)			
<i>HIGH PERFORMANCE</i>			



Attenuation Value	Length A
1-12 dB	0.90
13-30 dB	1.03

DC - 12.4 GHz		291 Series	Model Numbers
Male/Female	Female/Female	Male/Male	
ATT-0291-XX-SMA-02	ATT-291F-XX-SMA-02	ATT-291M-XX-SMA-02	
XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available)			
<i>HIGH PERFORMANCE</i>			



Attenuation Value	Length A
1-12 dB	0.98
13-30 dB	1.12

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Attenuators - Interconnects](#) category:*

*Click to view products by [Bel Fuse](#) manufacturer:*

Other Similar products are found below :

[R414701000](#) [R411800121](#) [R413840115](#) [ATT-523F-05-SMA-02](#) [R413305000](#) [R411808121](#) [R412501124](#) [R414702000](#) [ATP8-10006KV](#)  
[R414705000](#) [R411710124](#) [R410220121](#) [CT3369A-20](#) [09AS102-K40S3](#) [R411802000](#) [ATT-263F-03-SMA-02](#) [R417320130](#) [R412508124](#)  
[R417030110](#) [ATT-523F-12-SMA-02](#) [ATT-263F-06-SMA-02](#) [ATT-0263-22-SMA-02](#) [ATT-263F-10-SMA-02](#) [ATT-523F-10-SMA-02](#)  
[R422030020](#) [R422020030](#) [R417506130](#) [ATT-0263-25-SMA-02](#) [R413810000](#) [R411810124](#) [R413803000](#) [R417330110](#) [ATT-0290-02-HEX-](#)  
[02](#) [R415603000](#) [R415620000](#) [R415606000](#) [R415610000](#) [ATT-0290-00-SMA-02](#) [AT-130V](#) [CATTEN-05R0-BNC](#) [CATTEN-04R0-BNC](#)  
[6620\\_SMA-50-1/199\\_NE](#) [6630\\_SMA-50-2/199\\_NE](#) [CATTEN-06R0-BNC](#) [ATT-0294-02-SMA-02](#) [ATT-0298-06-HEX-02](#) [6610\\_SMA-50-](#)  
[2/199\\_NE](#) [6605\\_SMA-50-1/199\\_NE](#) [6820.17.A](#) [6803.17.B](#)