

Attenuators

SMA Subminiature "MINIPAD"®

| DC - 8.0 GHz | | 292 Series | Model Numbers |
|--|--|------------------------------------|------------------------------------|
| Male/Female | | Female/Female | Male/Male |
| ATT-0292-XX-SMA-02 | | ATT-292F-XX-SMA-02 | ATT-292M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available) | | | |
| HIGH PERFORMANCE | | | |



| DC - 2.0 GHz | | 294 Series | Model Numbers |
|--|--|------------------------------------|------------------------------------|
| Male/Female | | Female/Female | Male/Male |
| ATT-0294-XX-SMA-02 | | ATT-294F-XX-SMA-02 | ATT-294M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available) | | | |
| HIGH PERFORMANCE | | | |

LOW VSWR - Type II High Performance Attenuators

| DC - 18.0 GHz | | 451 Series | Model Numbers |
|---|--|------------------------------------|------------------------------------|
| Male/Female | | Female/Female | Male/Male |
| ATT-0451-XX-SMA-02 | | ATT-451F-XX-SMA-02 | ATT-451M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-30dB in 1dB increments | | | |
| LOW VSWR - see improved performance specifications on page 10. | | | |



| Attenuation Value | Length A |
|-------------------|----------|
| 1-12 dB | 0.86 |
| 13-30 dB | 1.02 |

| DC - 12.4 GHz | | 452 Series | Model Numbers |
|---|--|------------------------------------|------------------------------------|
| Male/Female | | Female/Female | Male/Male |
| ATT-0452-XX-SMA-02 | | ATT-452F-XX-SMA-02 | ATT-452M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-30dB in 1dB increments | | | |
| LOW VSWR - see improved performance specifications on page 10. | | | |



| Attenuation Value | Length A |
|-------------------|----------|
| 1-12 dB | 0.90 |
| 13-30 dB | 1.03 |

| DC - 4.0 GHz | | 454 Series | Model Numbers |
|---|--|------------------------------------|------------------------------------|
| Male/Female | | Female/Female | Male/Male |
| ATT-0454-XX-SMA-02 | | ATT-454F-XX-SMA-02 | ATT-454M-XX-SMA-02 |
| XX = Attenuation Value: Select 01-30dB in 1dB increments | | | |
| LOW VSWR - see improved performance specifications on page 10. | | | |



| Attenuation Value | Length A |
|-------------------|----------|
| 1-12 dB | 0.98 |
| 13-30 dB | 1.12 |

Note : 1. Low VSWR Models are available in Hex Body - Designate by substituting "HEX" for "SMA" in Model No.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Attenuators - Interconnects](#) category:

Click to view products by [Bel Fuse](#) manufacturer:

Other Similar products are found below :

[R411803119](#) [R413806115](#) [R413808000](#) [R413810115](#) [R413850115](#) [R414510000](#) [R414701000](#) [BNC-13](#) [R411800121](#) [R411801121](#)
[R412412124](#) [R412450000](#) [R413800000](#) [R413805000](#) [R413830000](#) [R413840115](#) [R414730000](#) [R415420000](#) [R415703000](#) [R416010000](#)
[R420003110](#) [R411801000](#) [R411815121](#) [R413305000](#) [R413801000](#) [R414520000](#) [R411808121](#) [R412500124](#) [R412414124](#) [R412501124](#)
[HMC-C584](#) [R413802000](#) [R412400124](#) [R411700124](#) [R417310130](#) [R411801119](#) [R412419124](#) [R411703124](#) [R412401124](#) [R443131000](#)
[R417130110](#) [R414700000](#) [R414505000](#) [R411802119](#) [R417720128](#) [R420706110](#) [R413811000](#) [R413803115](#) [R414501000](#) [R417903128](#)