

Stratos

SPLC-20-4-1-B-R6 Optical Transceiver

Connectivity for
Business Critical Continuity™

Gigabit Ethernet / Fiber Channel Applications
850nm SFP – 1.25 / 1.0625 GBaud - +3.3V



Product Overview

The Emerson Network Power Connectivity Solutions SPLC-20-4-1-B-R6 pluggable transceiver module is a high performance integrated duplex data link for bi-directional communication over multimode optical fiber. It is compliant with the MSA Small Form Factor Pluggable (SFP) specification. The SPLC-20-4-1-B-R6 is specifically designed for high speed Gigabit Ethernet/Fiber Channel applications. The Stratos Lightwave SFP transceiver is a hot pluggable which allows a suitably designed enclosure to be changed from one type of external interface to another simply by plugging in a SFP having the alternative external interface. The SPLC-20-4-2M-Bx-R6 operates at +3.3V. This optoelectronic transceiver module is a Class 1 Laser product compliant with FDA Radiation Performance Standards, 21 CFR Subchapter J. This component is also a Class 1 Laser compliant according to the International Safety Standard IEC-825-1.

Ordering Information

SPLC - 20 - 4 - 1 - B - R6

Key Features & Benefits

- 1.25/1.0625 GBaud Gigabit Ethernet/Fiber Channel Compliant
- Compliant with IEEE 802.3z 1000BASE_SX Specification for Optical Links
- Compliant with ANSI X3T11 Fiber Channel Specification
- Compliant with MSA SFP Specification
- 100Ω Differential AC Coupled CML Outputs
- Die Cast Metal Housing
- Hot Pluggable
- Single +3.3V Power Supply
- Serial ID Functionality
- RoHS Compliant

Module Specifications – Electrical: -5°C<Tc<+80°C; +3.0V<Vcc<+3.6V

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
Supply Current	Icc		180	250	mA	Tc = 25°C, Vcc = +3.3V
Surge Current	I _{surge}			300 30	mA	-5°C<Tc<+80°C; +3.15V<Vcc<+3.45V Surge above steady value
Transmitter						
PECL/CML Inputs (Differential)		400		2500	mVpp	AC Coupled Inputs
Input Impedance (Differential)	Z _{in}	85	100	115	Ω	R _{in} > 100KΩ @ DC
TX_DISABLE Input Voltage – High	ViH	2		3.45	V	
TX_DISABLE Input Voltage – Low	ViL	0		0.8	V	
TX_FAULT Output Voltage – High	VtoH	Vcc-0.5		Vcc+0.3	V	I _o = 400μA; Host Vcc
TX_FAULT Output Voltage – Low	VtoL	0		0.8	V	I _o = -4.0mA

Stratos

SPLC-20-4-1-B-R6 Optical Transceiver

Connectivity for
Business-Critical Continuity™

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
Receiver						
CML Outputs (Differential)		400	800	1200	mVpp	AC Coupled Outputs
Output Impedance (Differential)	Zout	85	100	115	Ω	
RX_LOS Output Voltage – High	VroH	Vcc-0.5		Vcc+0.3	V	Io = 400μA; Host Vcc
RX_LOS Output Voltage – Low	VroL	0		0.8	V	Io = -4.0mA
Total Jitter [pk-pk]	Tj			130	pS	Measured with 2 ⁷ -1 PRBS
MOD_DEF (0:2)	VoH VoL	2.5 0		Vcc+0.3 0.5	V	With Serial ID

Module Specifications – Optical: -5°C<Tc<+80°C; +3.0V<Vcc<+3.6V

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
50μm Core Diameter MMF		550	1000		m	BER<1.0E-12 @ 1.25/1.0625GBaud
62.5μm Core Diameter MMF		300	500		m	BER<1.0E-12 @ 1.25/1.0625GBaud
Transmitter						
Optical Center Wavelength	λ	830	850	860	nm	
Spectral Width	Δλ			0.85	nm	RMS
Optical Transmit Power	Popt	-9.5		-3	dBm	Average power @ 850nm
Optical Modulation Amplitude	OMA	180			μW	pk-pk
Extinction Ratio	ER	9			dB	P1/P0
Relative Intensity Noise	RIN			-117	dB/Hz	
Total Jitter [pk-pk]	Tj			170	ps	Measured with 2 ⁷ -1 PRBS
Output Rise/Fall Time	t _r , t _f			260	ps	20%-80%; Measured unfiltered
Receiver						
Optical Input Wavelength	λ	770		860	nm	
Optical Input Power	Pr	-17		0	dBm	BER<1.0E-12 @ 1.25/1.0625GBaud
Optical Modulation Amplitude	OMA	31			μW	pk-pk
Optical Return Loss	ORL	12			dB	
RX_LOS – Asserted	Pa	-29			dBm	Measured on transition – Low to High
RX_LOS – Deasserted	Pd			-17	dBm	Measured on transition – High to Low
RX_LOS – Hysteresis	Pa-Pd		1.5	5	dB	

For more information on this product consult the SPLC-20-4-1-B-R6 product data sheet.

IMPORTANT NOTICE

Stratos International, Inc. reserves the right to make changes to or discontinue any optical link product or service identified in this publication, without notice. Stratos International, Inc. recommends that its customers obtain the latest version of the publications to verify, before placing orders, that the information being relied on is current. Stratos International, Inc. warrants performance of its optical link products to current specifications in accordance with the Stratos International, Inc. standard warranty. Testing and other quality control techniques are utilized to the extent that Stratos International, Inc. has determined it to be necessary to support this warranty. Specific testing of all parameters of each optical link product is not necessarily performed on all optical link products. Stratos International, Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of a Stratos International, Inc. product can reasonably be expected to result in a personal injury. Stratos International, Inc. customers using or selling optical link products for use in such applications do so at their own risk and agree to fully indemnify Stratos International, Inc. for any damages resulting from such improper use or sale. Stratos International, Inc. assumes no liability for Stratos International, Inc. applications assistance, customer product design, software performance, or infringement of patents or services described here in. Nor does Stratos International, Inc. warrant or represent that a license, either expressed or implied is granted under any patent right, copyright, or intellectual property right, and makes no representations or warranties that these products are free from patent, copyright, or intellectual property rights. Applications that are described herein for any of the optical link products are for illustrative purposes only. Stratos International, Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Transmitters, Receivers, Transceivers](#) category:

Click to view products by [Bel Fuse](#) manufacturer:

Other Similar products are found below :

[STV.2413-574-00262](#) [TRPRG1VA1C000E2G](#) [TOTX1350\(V,F\)](#) [FTLX3813M349](#) [SCN-1428SC](#) [LTK-ST11MB](#) [HFD8003-002/XBA](#)
[HFD3020-500-ABA](#) [FTLF1429P3BCVA](#) [S6846](#) [SCN-2638SC](#) [FTLC9555FEPM](#) [TQS-QG4H9-J83](#) [SCN-1570SC](#) [SCN-1601SC](#) [SCN-](#)
[1338SC](#) [SFPPT-SR3-01](#) [HFD8003-500-XBA](#) [SCN-1383SC](#) [2333569-1](#) [LNK-ST11HB-R6](#) [FTL4C1QL3L](#) [FTL4C1QE3L](#) [FTL4C1QL3C](#)
[SPTSHP3PMCDF](#) [SPTSBP4LLCDF](#) [SPTMBP1PMCDF](#) [SPTSHP2PMCDF](#) [SF-NLNAMB0001](#) [SPTSLLP2SLCDF](#) [SPTSQP4LLCDF](#)
[1019682](#) [1019683](#) [1019705](#) [HFBR-1415Z](#) [AFBR-5803ATQZ](#) [AFBR-5803ATZ](#) [PLR135/T9](#) [TGW-Q14BB-FCQ](#) [AFBR-5803AZ](#) [TQS-](#)
[Q1LH8-XCA03](#) [TQS-Q1LH8-XCA05](#) [TQS-Q1LH8-XCA10](#) [TQS-Q1LH9-2CA](#) [HFBR-1414Z](#) [HFBR-1527Z](#) [HFBR-1528Z](#) [HFBR-2406Z](#)
[HFBR-2505AZ](#) [HFBR-2532Z](#)