# **Terminations**

## **SMA Miniature Male Plug**

### Ultra Short - 0.5 Watt High Performance

- DC 2, DC 8, DC 12.4, DC 18, and DC 26.5GHz units available
- Low VSWR
- Rugged Stainless Steel Construction
- Small Size, Light Weight
- Bead Chain available on all Models

Midwest Microwave's SMA miniature series of high performance coaxial Terminations provide temperature stable, ruggedly built, low VSWR precision performance in a compact light weight package size. Bead Chains are available with any of the units described.

#### SPECIFICATIONS

#### Impedance: 50 Ohms

Frequency: DC - 26.5, DC - 18.0, DC - 12.4., DC - 8.0, and DC - 2.0 GHz VSWR: 1.05 + 0.008 f (GHz) max @ DC - 18.0 GHz, 1.30 max @ 18 - 26.5 GHz Power: 0.5 Watts max @ 25 °C Operating Temperature Range: -65 to +125 °C

Finish: Passivated Stainless Steel






DC - 26.5 GHz	2443	Series	Model Numbers
Male Plug		Male	Plug with Chain
TRM-2443-M0-SMA-02	2	TRM-	2443-MC-SMA-02


DC - 18 GHz	2444	I Series	Model Numbers
Male Plug		Male	Plug with Chain
TRM-2444-M0-SMA-02		TRM-	2444-MC-SMA-02

DC - 12.4 GHz	2445	Series	Model Numbers
Male Plug		Male	e Plug with Chain
TRM-2445-M0-SMA-0	)2	TRM	-2445-MC-SMA-02

DC - 8.0 GHz	2446	Series	Model Numbers
Male Plug		Male	e Plug with Chain
TRM-2446-M0-SMA-	·02	TRM-	2446-MC-SMA-02

DC - 2.0 GHz	2447	Series	Model Numbers
Male Plug		Mal	e Plug with Chain
TRM-2447-M0-SMA-	-02	TRM	-2447-MC-SMA-02







## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Bel Fuse manufacturer:

Other Similar products are found below :

M390303-02N M39030/3-04S M39030/3-09S M39030/3-11N TNG1-9-78-D3 TNA2-50 TNG1-6-78 TNH1-1-50 TNGFL1-1-78 R4042N5000 53S1RR-001N3 142275 56S1RR-001N4 65\_BNC-50-0-7/133\_NE 71S1RR-001N4 02S17R-001D3 R404240120 R404260000 HT-10-2 FL LCX 50-OHM-RSMA M39030/3-04N TNA1-6-50 131-3801-811 TNA1-1-50 65\_N-50-0-51/113\_NE 65\_BNC-50-0-2/133\_NE 65\_N-50-0-1/133\_NE 65002\_N-50-1/122\_NE 65\_MMCX-50-0-31/111\_OE 18K15R-0.5E3 2702702 TRM-2161-M0-35M-02 53S17R-001N3 1100.19.0001 6701.01.B 18S24H-40ML5 TRM-2053-M0-NNN-02 R404759000 M39030/6-02N TRM-2080-M0-NNN-07 TRM-2053-MC-NNN-02 M39030/3-03S SF8012-6009 6701.01.A 65\_MCX-50-0-4/111\_NE 65\_716-50-0-2/003\_-E 65\_SMB-50-0-1/111\_NE M39030/3-12N 82-5722-RFX 8018-6174