

Electrical Characteristics

Frequency Range Nominal Impedance:

Operating Voltage (rms):

Dielectric Withstand Voltage (rms): Contact Resistance:

1.35.1 maximum DC to 1 GHz

1500 V maximum at sea level 5000 megohms minimum 1.5 milliohms maximum

500 V maximum at sea level

0.1 dB at 1 GHz

Conform to MIL-C-39012 500 cycles minimum

Environmental Characteristics

Temperature Range:

-65 °C to +165 °C

	PART	DESCRIPTION
_	Body	Brass, nickel plated 2.54 µm
2	Ferrule	Brass, nickel plated 2.54μm
З	Contact	Brass, gold plated 0.076μm - 0.127μm
4	Dielectric	PTFE

BNC Crimp Plug for RG179, RG187, BT3002, TZC75024, and PSF1/7M PART NUMBER:

APPVD

DATE

Ą Ą

> N ω

Б

SS

VB10-2062

PAGE 1 of 1

COPYRIGHT (C) 2002 VITELEC ELECTRONICS LIMITED

ACTWORK TOWER

otherwise stated

18 Jan 02

THIS DRAWING MAY NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT OUR WRITTEN PERMISSION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Bel Fuse manufacturer:

Other Similar products are found below:

8915-1511-000 89674-0827 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39030/3-01N 6500-7071-046 6769 CX050L2AQ 7002-1541-010 7002-1542-011 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7145-1521-002 7203-1571-003 7209-1511-011 7210-1511-015 7210-1511-019 73137-5015 73216-2241 73404-2300 7405-1521-005 7405-1521-802 8527 8547 FS11V 877931 8808-1511-001 9049-9513-000 9074-9513-000 9101-9573-002 910A205F 9130-9573-002 PL11SC-026 PL375-33 PL40-5 PL74C-221 PL75MC-217 PL803-7 980-8666-005 1200690078 1-201144-1 R107003010W